

THIRD EDITION



Materials

ENGINEERING, SCIENCE,
PROCESSING AND DESIGN

Michael Ashby, Hugh Shercliff and David Cebon



**B
H**

Materials: engineering, science, processing and design

Third edition

Mike Ashby, Hugh Shercliff, and David Cebon

Department of Engineering, University of Cambridge, UK



AMSTERDAM • BOSTON • HEIDELBERG • LONDON
NEW YORK • OXFORD • PARIS • SAN DIEGO
SAN FRANCISCO • SINGAPORE • SYDNEY • TOKYO
Butterworth-Heinemann is an imprint of Elsevier



Contents

Preface to the 3rd edition	xiii
Acknowledgements	xvii
Resources that accompany this book	xix
Chapter 1 Introduction: materials—history and character	1
1.1 Materials, processes and choice	2
1.2 Material properties	4
1.3 Design-limiting properties	12
1.4 Summary and conclusions	13
1.5 Further reading	13
1.6 Exercises	13
Chapter 2 Family trees: organising materials and processes	15
2.1 Introduction and synopsis	16
2.2 Getting materials organised: the materials tree	16
2.3 Organising processes: the process tree	19
2.4 Process-property interaction	23
2.5 Material property charts	23
2.6 Computer-aided information management for materials and processes	26
2.7 Summary and conclusions	28
2.8 Further reading	29
2.9 Exercises	29
2.10 Exploring design using CES	31
2.11 Exploring the science with CES Elements	31
Chapter 3 Strategic thinking: matching material to design	33
3.1 Introduction and synopsis	34
3.2 The design process	34
3.3 Material and process information for design	37
3.4 The strategy: translation, screening, ranking and documentation	38
3.5 Examples of translation	42
3.6 Summary and conclusions	46
3.7 Further reading	47

Contents

Preface to the 3rd edition	xiii
Acknowledgements	xvii
Resources that accompany this book	xix
Chapter 1 Introduction: materials—history and character	1
1.1 Materials, processes and choice	2
1.2 Material properties	4
1.3 Design-limiting properties	12
1.4 Summary and conclusions	13
1.5 Further reading	13
1.6 Exercises	13
Chapter 2 Family trees: organising materials and processes	15
2.1 Introduction and synopsis	16
2.2 Getting materials organised: the materials tree	16
2.3 Organising processes: the process tree	19
2.4 Process-property interaction	23
2.5 Material property charts	23
2.6 Computer-aided information management for materials and processes	26
2.7 Summary and conclusions	28
2.8 Further reading	29
2.9 Exercises	29
2.10 Exploring design using CES	31
2.11 Exploring the science with CES Elements	31
Chapter 3 Strategic thinking: matching material to design	33
3.1 Introduction and synopsis	34
3.2 The design process	34
3.3 Material and process information for design	37
3.4 The strategy: translation, screening, ranking and documentation	38
3.5 Examples of translation	42
3.6 Summary and conclusions	46
3.7 Further reading	47

3.8	Exercises	47
3.9	Exploring design using CES	49
Chapter 4 Stiffness and weight: density and elastic moduli		51
4.1	Introduction and synopsis	52
4.2	Density, stress, strain and moduli	52
4.3	The big picture: material property charts	63
4.4	The science: what determines stiffness and density?	65
4.5	Manipulating the modulus and density	77
4.6	Acoustic properties	80
4.7	Summary and conclusions	84
4.8	Further reading	86
4.9	Exercises	87
4.10	Exploring design with CES	92
4.11	Exploring the science with CES Elements	93
Chapter 5 Flex, sag and wobble: stiffness-limited design		95
5.1	Introduction and synopsis	96
5.2	Standard solutions to elastic problems	96
5.3	Material indices for elastic design	105
5.4	Plotting limits and indices on charts	111
5.5	Case studies	115
5.6	Summary and conclusions	122
5.7	Further reading	122
5.8	Exercises	123
5.9	Exploring design with CES	127
5.10	Exploring the science with CES Elements	128
Chapter 6 Beyond elasticity: plasticity, yielding and ductility		129
6.1	Introduction and synopsis	130
6.2	Strength, plastic work and ductility: definition and measurement	130
6.3	The big picture: charts for yield strength	137
6.4	Drilling down: the origins of strength and ductility	138
6.5	Manipulating strength	148
6.6	Summary and conclusions	156
6.7	Further reading	157
6.8	Exercises	158
6.9	Exploring design with CES	162
6.10	Exploring the science with CES Elements	162

Chapter 7 Bend and crush: strength-limited design	165
7.1 Introduction and synopsis	165
7.2 Standard solutions to plastic problems	166
7.3 Material indices for yield-limited design	175
7.4 Case studies	179
7.5 Summary and conclusions	185
7.6 Further reading	185
7.7 Exercises	186
7.8 Exploring design with CES	193
Chapter 8 Fracture and fracture toughness	197
8.1 Introduction and synopsis	198
8.2 Strength and toughness	198
8.3 The mechanics of fracture	200
8.4 Material property charts for toughness	207
8.5 Drilling down: the origins of toughness	209
8.6 Compressive and tensile failure of ceramics	212
8.7 Manipulating properties: the strength–toughness trade-off	217
8.8 Summary and conclusions	220
8.9 Further reading	220
8.10 Exercises	221
8.11 Exploring design with CES	223
8.12 Exploring the science with CES Elements	224
Chapter 9 Shake, rattle and roll: cyclic loading, damage and failure	225
9.1 Introduction and synopsis	226
9.2 Vibration and resonance: the damping coefficient	226
9.3 Fatigue	227
9.4 Charts for endurance limit	235
9.5 Drilling down: the origins of damping and fatigue	236
9.6 Manipulating resistance to fatigue	238
9.7 Summary and conclusions	240
9.8 Further reading	240
9.9 Exercises	240
9.10 Exploring design with CES	245
Chapter 10 Keeping it all together: fracture-limited design	247
10.1 Introduction and synopsis	248
10.2 Standard solutions to fracture problems	248
10.3 Material indices for fracture-safe design	249
10.4 Case studies	252
10.5 Summary and conclusions	264

10.6	Further reading	265
10.7	Exercises	265
10.8	Exploring design with CES	270
Chapter 11 Rub, slither and seize: friction and wear		273
11.1	Introduction and synopsis	274
11.2	Tribological properties	274
11.3	Charting friction and wear	276
11.4	The physics of friction and wear	278
11.5	Friction in design and metal processing	282
11.6	Summary and conclusions	288
11.7	Further reading	289
11.8	Exercises	289
11.9	Exploring design with CES	291
Chapter 12 Agitated atoms: materials and heat		293
12.1	Introduction and synopsis	294
12.2	Thermal properties: definition and measurement	294
12.3	The big picture: thermal property charts	298
12.4	Drilling down: the physics of thermal properties	301
12.5	Manipulating thermal properties	306
12.6	Design and manufacture: using thermal properties	307
12.7	Summary and conclusions	320
12.8	Further reading	321
12.9	Exercises	321
12.10	Exploring design with CES	324
12.11	Exploring the science with CES Elements	325
Chapter 13 Running hot: using materials at high temperatures		329
13.1	Introduction and synopsis	330
13.2	The temperature dependence of material properties	330
13.3	Charts for creep behaviour	336
13.4	The science: diffusion	339
13.5	The science: creep	347
13.6	Materials to resist creep	354
13.7	Design to cope with creep	356
13.8	Summary and conclusions	363
13.9	Further reading	364
13.10	Exercises	365
13.11	Exploring design with CES	372
13.12	Exploring the science with CES Elements	373
		375

Chapter 14 Conductors, insulators and dielectrics	375
14.1 Introduction and synopsis	376
14.2 Conductors, insulators and dielectrics	377
14.3 Charts for electrical properties	385
14.4 Drilling down: the origins and manipulation of electrical properties	388
14.5 Design: using the electrical properties of materials	402
14.6 Summary and conclusions	408
14.7 Further reading	409
14.8 Exercises	409
14.9 Exploring design with CES	413
14.10 Exploring the science with CES Elements	414
Chapter 15 Magnetic materials	417
15.1 Introduction and synopsis	418
15.2 Magnetic properties: definition and measurement	418
15.3 The big picture: charts for magnetic properties	424
15.4 Drilling down: the physics and manipulation of magnetic properties	428
15.5 Materials selection for magnetic design	433
15.6 Summary and conclusions	441
15.7 Further reading	441
15.8 Exercises	442
15.9 Exploring design with CES	444
15.10 Exploring the science with CES Elements	445
Chapter 16 Materials for optical devices	447
16.1 Introduction and synopsis	448
16.2 The interaction of materials and radiation	448
16.3 Charts for optical properties	456
16.4 Drilling down: the physics and manipulation of optical properties	458
16.5 Optical design	465
16.6 Summary and conclusions	468
16.7 Further reading	468
16.8 Exercises	469
16.9 Exploring design using CES	471
16.10 Exploring the science with CES Elements	472
Chapter 17 Durability: oxidation, corrosion, degradation	473
17.1 Introduction and synopsis	474
17.2 Oxidation, flammability and photo-degradation	475
17.3 Oxidation mechanisms	477
17.4 Resistance to oxidation, burning and photo-degradation	480
17.5 Corrosion: acids, alkalis, water and organic solvents	482

17.6	Drilling down: mechanisms of corrosion	483
17.7	Fighting corrosion	493
17.8	Summary and conclusions	506
17.9	Further reading and software	506
17.10	Exercises	507
17.11	Exploring design with CES	510
17.12	Exploring the science with CES Elements	512

Chapter 18 Heat, beat, stick and polish: manufacturing processes 513

18.1	Introduction and synopsis	514
18.2	Process selection in design	514
18.3	Process attributes: material compatibility	516
18.4	Shaping processes: attributes and origins	518
18.5	Joining processes: attributes and origins	526
18.6	Surface treatment (finishing) processes: attributes and origins	529
18.7	Estimating cost for shaping processes	530
18.8	Computer-aided process selection	533
18.9	Case studies	536
18.10	Summary and conclusions	545
18.11	Further reading	545
18.12	Exercises	546
18.13	Exploring design with CES	548
18.14	Exploring the science with CES Elements	550

Chapter 19 Follow the recipe: processing and properties 551

19.1	Introduction and synopsis	552
19.2	Processing for properties	553
19.3	Microstructure of materials	555
19.4	Microstructure evolution in processing	559
19.5	Metals processing	571
19.6	Non-metals processing	585
19.7	Making hybrid materials	589
19.8	Summary and conclusions	592
19.9	Further reading	592
19.10	Exercises	593
19.11	Exploring design with CES	595

Chapter 20 Materials, processes and the environment 597

20.1	Introduction and synopsis	598
20.2	Material consumption and its growth	598
20.3	The material life cycle and criteria for assessment	602
20.4	Definitions and measurement: embodied energy, process energy and recycling energy	606

20.5	Charts for embodied energy	611
20.6	Design: selecting materials for eco-design	614
20.7	Materials and sustainability	619
20.8	Summary and conclusions	629
20.9	Appendix: some useful quantities	629
20.10	Further reading	630
20.11	Exercises	631
20.12	Exploring design with CES	635
20.13	Exercises on sustainability	636

Guided Learning Unit 1: Simple ideas of crystallography

GL1-1

Introduction and synopsis	GL1-2
PART 1 Crystal structures	GL1-2
PART 2 Interstitial space	GL1-9
PART 3 Describing planes	GL1-11
PART 4 Describing directions	GL1-13
PART 5 Ceramic crystals	GL1-14
PART 6 Polymer crystals	GL1-19
Answers to exercises	GL1-20

Guided Learning Unit 2: Phase diagrams and phase transformations

GL2-1

Introduction and synopsis	GL2-2
PART 1 Key terminology	GL2-3
PART 2 Simple phase diagrams, and how to read them	GL2-7
PART 3 The iron-carbon diagram	GL2-23
PART 4 Interpreting more complex phase diagrams	GL2-27
PART 5 Phase transformations and microstructural evolution	GL2-34
PART 6 Equilibrium solidification	GL2-36
PART 7 Equilibrium solid-state phase changes	GL2-49
PART 8 Non-equilibrium solid-state phase changes	GL2-55
Further reading	GL2-64
Further exercises	GL2-65

Appendix Data for engineering materials

A-1

Index

I-1

Index

Note: Page numbers with “f” denote figures; “t” tables; and “b” boxes.

A

abrasive wear, 280, 280f

ABS. *See* Acrylonitrile butadiene styrene

Absorption, 9f, 449–450

mechanisms of, 82
sound, 86

Absorptivity, 448

Acetone (CH_3COCH_3), 483

Acoustic properties

sound, 80–81
energy radiation, 83–84
management, 82–83
velocity and wavelength, 81–82
wave impedance, 83–84
from ultra-sonic to seismic, 81f
visualising, 84

acrylonitrile butadiene styrene (ABS), 27f, 587

activation energy for self-diffusion, 340

active coatings, 501

See also Passive coatings

adhesive wear, 280

Airframes

aerodynamic heating, 361
stress–temperature profile, 359f
supersonic flight, 361
thermal stress, 361
turbine blade with TBC, 360f
wing-tip displacement, 362

Al–Cu system. *See* Aluminum-copper system

Allotropes, 319

Alloy(s), 561

applications, A-2
binary, GL2-3b
constitution of, GL2-5–GL2-6
corrosion-resistant, 356
ductility, 154
metallic, GL2-33
melts and heat treatment, 583

Alnico alloy, 437

α -iron

See also Ferrite

Alumina (Al_2O_3), GL1-17–GL1-18

Aluminium-copper system, GL2-17f, GL2-18

Aluminum

alloys, 16–17
bike frames, 553
finished products, 555
interactions, 555
materials processing, 553
temperature cycle, 553–555
unintended side-effects, 555

laminates, 591–592

Aluminum-copper system (Al–Cu system), 563–564

phase diagram for, 563f

Amorphous metal alloy (AMA), 438

Amorphous silica, 69f

Anisotropic solids, elastically, 82

Anisotropy, 65

Anodising, 480–481

Anti-ferro-magnets, 429–430

Arsenic (III) oxide (As_2O_3), 504

Atom packing

in ceramics, 68
fraction, GL1-7
for FCC lattice, GL1-7b
in glasses, 68
in metals, 65–66
amorphous structures, 67f
balls on pool table, 65f
crystal lattice, 67
square grid of spheres, 66f
structures, 66
and unit cell, 66

in polymers

common polymers, 70f
elastomers, 72
polymer chains, 69f
polymer molecules bond, 69–71

Atom packing (*Continued*)

- polymer structures, 69
- spaghetti-like tangles, 71f
- structures for silica, 69f
- thermoplastics weak bonds, 71

B

Bar charts, 24

- embodied energy, 611
 - of basic materials by volume, 612f
 - of basic materials by weight, 612f
- modulus, 24f
- usage, 24b

Barium titanate (BaTiO_3), 400

Batch processes, 523

Beam elastic bending

- cross-section area and second moments, 100f
- deflection, 100f
- using distance, 98–99
- distributions, 100–102
- example, 98b, 101b
- neutral axis, 98
- stiffness calculation, 99

Beam theory, 103

Bearing(s), 282

- plane, 284
- pressure, 278
- sliding, 282
- white-metal, 284

Beer-Lambert law, 482

Bendy design

- elastic or natural hinges, 121f
- elasticity, 120
- exploiting elasticity, 120
- flexural degrees of freedom, 121f
- sliding mechanism, 120f
- spring-loaded plunger, 120
- strength, 121
- traditional three-part hinge, 120

Benzene (C_6H_6), 483

Benzophenone, 482

Benzotriazole, 482

Bi-metal corrosion cell, 489f

Bigger still, 598

Bill of materials, 610

Binary alloys, GL2-3b

- segregation in solidification, GL2-46f
- solid microstructure in, GL2-4
- solidification of, GL2-39

Binary diagram, GL2-9

- constitution point, GL2-10–GL2-12
- phase composition, GL2-12–GL2-13
- solidus boundaries, GL2-9
- tie-line, GL2-10–GL2-12

Binary lead-tin system (Pb-Sn system), 561

Bio-fuels, 621

Bio-polymers, 621

Blend, 156

Body-centred cubic (BCC), GL1-3f

- cubic unit cell, GL1-5
- metallic elements, GL1-5–GL1-6
- metals, GL1-6
- non-close-packed spheres, GL1-6f
- octahedral hole in, 23f
- tetrahedral hole, GL1-9f

Bond stiffnesses, 73

Boriding, 286

Boundary-layer lubrication, 282

Brake disks, 581, 581f

Brake linings, 285

Breakdown potential, 397–398

Brittle cleavage fracture, 210

Brownian motion, 339

Bubble chart, 25–26

- modulus, 25f
- usage, 25b

Buckling

- of columns and plates, 103, 104f
- natural vibration modes, 104f

Bulk modulus, 58

Bulk polymers, 77

Bumper crash barrier, 617f

C $\text{C}(\text{NH}_2)_2\text{S}$

See also Thiourea

Cable insulation, 402–403

Calcium bicarbonate ($\text{Ca}(\text{HCO}_3)_2$), 504

Calorimetry, 295

Cambridge Engineering Selector, 542–543

Capacitor, 380–382

Carbon fibre, 599

Carbon steels, 561, 577, 583

- cast irons and, GL2-24f
- heat-treatment, GL2-60
 - displacive transformation, GL2-60
 - hardenability, GL2-61–GL2-63
 - martensite, GL2-60, GL2-62f

- martensite transformation, GL2-61f
 - phase transformations, GL2-63
 - quench cracking, GL2-61–GL2-63
 - quenching and tempering effect, GL2-60–GL2-61
 - tempering, GL2-60
 - low, 578–579
 - phase transformations in, GL2-50
 - from FCC γ -iron to BCC α -iron, GL2-51f
 - nucleation, GL2-50
 - plain, 577, 578f
- Carbon taxes, 621
- Carbon tetrachloride (CCl_4), 483
- Carbon-fiber reinforced polymers (CFRP), 19, 115–116
- Carburising, 286, 345
- Cast irons, 581–582
 - brake disk, 581–582, 581f
 - high-silicon, 481
 - microstructures in, 582f
- Casting, 19, 571
 - alloys, GL2-55–GL2-56
 - processes, 523
- Cathodic protection, 497
- CCl_4 . *See* Carbon tetrachloride
- Cellular solids, 79
- Cementite. *See* Iron carbide (Fe_3C)
- Ceramic crystals, GL1-14
 - See also* Polymer; crystals
 - corundum structure, oxides with, GL1-17–GL1-18, GL1-18f
 - DC structure
 - Silicon carbide, GL1-15, GL1-16f
 - unit cell, GL1-15
 - fluorite structure, oxides with, GL1-18–GL1-19, GL1-18f
 - functional materials, GL1-15
 - Rocksalt structure
 - oxygen ions, GL1-16
 - Sodium chloride, GL1-16
- Ceramic matrix composite (CMC), 77
- Ceramic spark plug insulator shaping, 536, 537f
 - See also* Thermoplastic CD case shaping
 - constraints, 537–538
 - documentation search details, 538
 - powder methods, 538t
 - translation for, 537t
- Ceramic(s), 557
 - anisotropy, 65
 - applications, A-5
 - atom packing in, 68
 - ceramic-metal composites, 585
 - coatings, 502
 - compressive failure, 213–214
 - failure mechanisms, 213f
 - microstructure, 557f, 585
 - phase diagrams, GL2-28
 - mullite, GL2-28–GL2-29
 - silica-alumina system, GL2-28–GL2-29, GL2-30f
 - stress-strain curve for, 131f
 - tensile failure
 - bending strength, 217
 - example, 215b
 - flaw controls failure, 216–217
 - probability, 216
 - statistical distribution, 214
 - strength and toughness, 218f
 - survival probability, 215f
 - in tension and pure bending, 216f
 - Weibull equation, 215–216
 - Weibull statistics, 214
 - tensile stress-strain curves for, 57f
- Ceramics glasses composites, A-5
 - density, A-8
 - electrical resistivity and dielectric constant, A-18
 - fracture toughness, A-14
 - melting and glass temperature, A-6
 - thermal conductivity and expansion, A-16
 - yield and tensile strength, A-12
 - Young's modulus, A-10
- CES system
 - elements database, 342
 - exploring design using, 31
 - exploring science with, 31–32
 - software, 286
- CFRP. *See* Carbon-fiber reinforced polymers
- CH_3COCH_3 . *See* Acetone
- Charge density, 382
- Chemical segregation, 212
- Chemical vapor deposition (CVD), 465
- Chromates, 504
- Chromium-nickel system, GL2-30f
- Close-packed hexagonal (CPH), GL1-3f
 - dimensions, GL1-21f
 - HCP metals, GL1-4
 - HCP structure of packed spheres, GL1-4f
 - metallic elements, GL1-4

- Close-packed hexagonal (CPH) (*Continued*)
 - octahedral hole, 9f
 - packing, 65–66
 - tetrahedral holes, GL1-23f
- Close-packed layer, 65–66
- CMC. *See* Ceramic matrix composite
- CO₂ footprint, 606
- Coatings, 497
 - active, 501
 - ceramic and glass, 502
 - metallic, 501
 - passive, 500–501
 - polymeric, 501–502
 - self-generated, 501
 - ways, 503f
- Coefficient of friction, 274
 - Archard wear constant, 277f
 - sliding combinations, 276–277
 - unlubricated steel surface, 276f
- Coercive field–Curie temperature chart, 427
- Cohesive energy
 - atom-scale force-displacement response, 73
 - bond
 - energy, 72
 - stiffness, 72f
 - stiffnesses, 73
 - comparing, 73
 - foams or elastomers, 74
 - stress, 73
 - Young's modulus, 74
- Cold drawing, 146–147
- Combustion, 481
 - in free-radicals reaction, 481
- Components, GL2-3b
 - in carbon steel, GL2-3
 - weight and atom, GL2-4
- Composites, 591
 - applications, A-5
 - boundaries, 78
 - composite density, 78
 - example, 78b
 - fibre-reinforced polymers, 79
 - geometry or shape, 78
 - manipulation, 77f
 - reinforcement, 79f
 - strength–toughness, 217–218
- Computer-aided design, 3
- Computer-aided information management
 - computer-based resources, 26b
 - injection moulding, 27f
 - software, 26–28
- Computer-aided selection, 113
 - bar chart with CES software, 536f
 - batch-process cost model, 534–535
 - using CES software, 113–115
 - database, 533–534
 - output of cost model, 535f
 - screening steps, 535f
 - selection, 533
 - selection window, 114f
- Computer-based resources, 26b
- Condensers. *See* Capacitor
- Conductivity, 377–378
- Constitution
 - of alloy, GL2-5–GL2-6
 - constitutive model, 334–335
 - equilibrium constitution, GL2-5
 - point, GL2-10–GL2-12
- Constraints, 514
- Constructive interference, 454–456.
 - See also* Destructive interference
- Consumption of materials. *See* Material consumption
- Contact stresses, 172
- Continuous use temperature (CUT), 330
- Corkscrew lever, 115f
 - design requirements for, 116t
 - strength, 180
 - translation for, 43t
- Corrosion
 - alkalis, 482–483
 - cell, 489–490
 - combating corrosion, 483
 - fatigue, 493
 - fresh and impure water, 487
 - bi-metal corrosion cell, 489f
 - corrosion cell, 489
 - corrosion potential, 487–489
 - electro-plating, 490–491
 - galvanic series, 490
 - hydrolysis reaction, 491
 - oxygen dissolving, 491f
 - reduction potentials, 489
 - inhibitors, 504
 - As₂O₃, 504
 - C(NH₂)₂S, 504
 - Ca(HCO₃)₂, 504
 - chromates, 504

- polyphosphates, 504
- PTFE, 504
- ions in solution, 483
 - acids and alkalis, 486
 - ionised water, 486
 - pH and pOH scales, 487f
 - sulfuric acid, 486
 - zinc, 486–487
- liquids environments, 482
- oils and organic solvents, 483
- oxygen, 482
- selective corrosion, 492
 - corrosion fatigue, 493
 - intergranular corrosion, 492
 - stress corrosion cracking, 492–493
- strong acids, 482
- Cost
 - model
 - capital cost of equipment, 530–532
 - cost of casting, 532–533, 533f
 - economic batch size, 533
 - manufacture of component, 530, 531f
 - overhead rate, 532
 - process–economic batch size bar chart, 534f
 - production rate, 532
 - symbols, definitions and units in, 531t
 - structural materials
 - for buildings, 117, 117f
 - corrosion resistance, 117
 - material index for, 118
 - for stiff floor beams, 118f
 - stone and brick, 119
- Couplings, 180–182
- Crack tip plastic zone, 204–205
 - approximate crack lengths for, 207t
 - brittle materials, 205
 - damage tolerance, 206–207
 - example, 206b
 - forms at crack tip, 205f
 - tensile failure stress, 206
 - transition from yield to fracture, 206f
- Cracked components, fatigue loading
 - crack growth during, 234f
 - cyclic loading, 233f
 - in fabricating large structures, 233
 - fatigue crack growth, 233
 - Paris law, 233–234
 - polystyrene ruler, 234b
 - safe design against fatigue failure, 234–235
- Crash barriers, 617
 - function of barrier, 617–618
 - material selection, 618f
 - minimum embodied energy, 617–618
 - mobile barrier selection, 618
 - static and bumper, 617f
 - static barrier selection, 618–619
 - stiffness-limited design, 619
- Creep, 330
 - airframes
 - aerodynamic heating, 361
 - stress–temperature profile, 359f
 - supersonic flight, 361
 - thermal stress, 361
 - turbine blade with TBC, 360f
 - wing-tip displacement, 362
 - creep fracture, 330
 - diffusion, 339
 - loads or pressure, 349
 - creep problems, 356
 - creep relaxation
 - adiabatic heating, 361f
 - creep strain, 362
 - pre-tensioned components, 362
 - strength of alloys, 362f
 - stress relaxation, 363f
 - creep-resistant alloys, 356
 - damage and fracture, 335
 - creep–rupture diagrams, 335
 - example, 336b
 - deformation, 332
 - example, 351b
 - mechanism diagrams, 349
 - for nickel alloy, 351f
 - diffusional flow
 - deformation, 348f
 - free volume, 352
 - polycrystalline, 342
 - dislocation climb, 347
 - high-temperature pipework, 356–357
 - materials, 355f
 - safety-critical component, 358
 - stress in pipe, 357
 - hot forming process, 332
 - in hot forming processes
 - hot forming temperatures, 350–352
 - shaping methods, 350
 - industrial applications, 356
 - metals and ceramics to resisting

- Creep (*Continued*)
- ceramics, 354
 - diffusional flow, 354
 - power-law creep, 354
 - modulus, 354
 - performance of materials, 356
 - polymers
 - creep rate, 355
 - crystalline materials, 349
 - glass temperature, 354
 - real polymers, 354
 - visco-elastic solids, 352
 - power-law creep, 333
 - TBC
 - ceramics, 360
 - gas turbines, 359
 - testing and curves, 333
 - activation energy for, 334
 - constitutive model, 334–335
 - creep rate, 334f
 - primary creep strains, 333
 - strain rate, 334
 - turbine blades
 - centrifugal forces, 358–359
 - pressurised pipe, 357f
 - strengthening methods, 359
 - stress, 358
 - stress–rupture time data, 357f
- Creep behaviour
- charts for, 336
 - creep strength
 - high-temperature design, 339
 - load-bearing structures, 338
 - titanium alloys, 339
 - melting point, 336
 - ceramics, metals and polymers, 337f
 - service temperature and strength, 338
- Creep strains, 333
- Creep–rupture diagrams, 335
- Crevices, 497
- Critical cooling rate, 35, 570
- Critical materials. *See* Strategic materials
- Critical strain energy release rate. *See* Toughness
- Crushing strength, compressive, 133
- Crystal lattices, three-dimensional, 2
- Crystal(s), 66
 - atomic packing fraction, 7
 - BCC, 3f
 - cubic unit cell, 5
 - metallic elements, 5–6
 - metals, 6
 - non-close-packed spheres, 6f
 - close-packed planes layers, 3f
 - CPH structure
 - HCP metals, 4
 - HCP structure of packed spheres, 4f
 - metallic elements, 4
 - FCC structure, 3f
 - cubic unit cell, 4
 - metallic elements, 5
 - metals, 5
 - packed spheres, 5f
 - lattice, 67
 - texture, 575
 - theoretical density, 8
 - three-dimensional crystal lattices, 2
 - unit cell, 2

Crystalline, 69f

 - materials, 148
 - solids, 75
 - state, 68–69

Crystalline imperfection, 140–141

 - defects in crystals, 141f
 - defects in metals and ceramics
 - dislocation, 142
 - grain boundaries, 142
 - impurities, 141
 - precision machine tool, 142

Crystallites, 71

Cubic cells, 67

Cumulative damage, 232

Cushions, 119

CUT. *See* Continuous use temperature

CVD. *See* Chemical vapor deposition

Cyclic loading, 226

 - crack growth during, 234f
 - cracked component, 233f

D

Damping

 - coefficient, 226–227
 - fatigue damage and cracking
 - dislocation motion, 237
 - in high-cycle fatigue, 237
 - in low-cycle fatigue, 238
 - material damping, 236–237

Defect control, 585

Deformation mechanism, 349

- Creep (*Continued*)
- ceramics, 354
 - diffusional flow, 354
 - power-law creep, 354
 - modulus, 354
 - performance of materials, 356
 - polymers
 - creep rate, 355
 - crystalline materials, 349
 - glass temperature, 354
 - real polymers, 354
 - visco-elastic solids, 352
 - power-law creep, 333
 - TBC
 - ceramics, 360
 - gas turbines, 359
 - testing and curves, 333
 - activation energy for, 334
 - constitutive model, 334–335
 - creep rate, 334f
 - primary creep strains, 333
 - strain rate, 334
 - turbine blades
 - centrifugal forces, 358–359
 - pressurised pipe, 357f
 - strengthening methods, 359
 - stress, 358
 - stress–rupture time data, 357f
- Creep behaviour
- charts for, 336
 - creep strength
 - high-temperature design, 339
 - load-bearing structures, 338
 - titanium alloys, 339
 - melting point, 336
 - ceramics, metals and polymers, 337f
 - service temperature and strength, 338
- Creep strains, 333
- Creep–rupture diagrams, 335
- Crevices, 497
- Critical cooling rate, 35, 570
- Critical materials. *See* Strategic materials
- Critical strain energy release rate. *See* Toughness
- Crushing strength, compressive, 133
- Crystal lattices, three-dimensional, 2
- Crystal(s), 66
 - atomic packing fraction, 7
 - BCC, 3f
 - cubic unit cell, 5
 - metallic elements, 5–6
 - metals, 6
 - non-close-packed spheres, 6f
 - close-packed planes layers, 3f
 - CPH structure
 - HCP metals, 4
 - HCP structure of packed spheres, 4f
 - metallic elements, 4
 - FCC structure, 3f
 - cubic unit cell, 4
 - metallic elements, 5
 - metals, 5
 - packed spheres, 5f
 - lattice, 67
 - texture, 575
 - theoretical density, 8
 - three-dimensional crystal lattices, 2
 - unit cell, 2
- Crystalline, 69f
 - materials, 148
 - solids, 75
 - state, 68–69
- Crystalline imperfection, 140–141
 - defects in crystals, 141f
 - defects in metals and ceramics
 - dislocation, 142
 - grain boundaries, 142
 - impurities, 141
 - precision machine tool, 142
- Crystallites, 71
- Cubic cells, 67
- Cumulative damage, 232
- Cushions, 119
- CUT. *See* Continuous use temperature
- CVD. *See* Chemical vapor deposition
- Cyclic loading, 226
 - crack growth during, 234f
 - cracked component, 233f
- D**
- Damping
 - coefficient, 226–227
 - fatigue damage and cracking
 - dislocation motion, 237
 - in high-cycle fatigue, 237
 - in low-cycle fatigue, 238
 - material damping, 236–237
- Defect control, 585
- Deformation mechanism, 349

- example, 351b
- for nickel alloy, 351f
- Density, 5–6, 52
 - applications, 52
 - by Archimedes' method, 53f
 - atom packing
 - amorphous structures, 67f
 - balls on pool table, 65f
 - in ceramics, 68
 - crystal lattice, 67
 - in glasses, 68–69
 - in metals, 65–66
 - in polymers, 69–72
 - square grid of spheres, 66f
 - structures, 66
 - and unit cell, 66
 - cohesive energy and elastic moduli, 72
 - atom-scale force-displacement response, 73
 - bond energy, 72
 - bond stiffness, 72f
 - bond stiffnesses, 73
 - comparing, 73
 - foams or elastomers, 74
 - stress, 73
 - Young's modulus, 74
 - crystallography, 65
 - glass transition temperature, 75
 - glassy, 75–76
 - modulus variation with temperature, 75f
 - polymer deformation, 76
 - metallic alloys modulus, 76–77
 - origin of density, 76
 - relative, 119
 - samples with regular shapes, 52–53
- Density manipulation
 - atomic packing and bonding, 77
 - composites, 77
 - boundaries, 78
 - composite density, 78
 - example, 78b
 - fibre-reinforced polymers, 79
 - geometry or shape, 78
 - manipulation, 77f
 - reinforcement, 79f
 - foams, 79
 - cellular solids, 79–80
 - foam modulus, 80
- Deposition process, 308
- Design for recycling, 621
- Design parameters, 96
- Design process, 34
 - devices to open corked bottles, 36
 - concepts, 36
 - embodiment sketches, 36
 - market need, 36f
 - documentation, 42
 - interaction, 39f
 - original design
 - conceptual and embodiment stages, 34–35
 - design flow chart, 35f
 - high-purity silicon, 34
 - product specification, 34
 - parallel route, 39
 - ranking, 41
 - redesign, 35–36
 - necessary changes, 36
 - using scenarios, 35
 - screening, 41
 - translation, 39–40
 - boundary conditions, 40
 - common constraints and objectives, 41t
 - constraints, objectives and free variables, 40t
 - distinctions, 40–41
 - examples, 42–46
 - outcome, 41
 - strategy applied to materials, 40f
- Design-limiting properties, 12
- Diamond cubic structure (DC structure), 15, 15f
 - Silicon carbide, 15, 16f
 - tetrahedral packing in, 25f
 - unit cell, 15
- Dichroic materials, 464–465
- Dielectric, 376
 - behaviour
 - dipole moments, 395–396, 396f
 - polar groups, 396
 - breakdown
 - breakdown potential, 397–398
 - kinetic energy, 397
 - lightning strike, 398f
 - constant, 8–9
 - loss, 396–397
 - water molecule, 397f
 - properties
 - breakdown field, 382–383
 - capacitor, 380–381
 - charge density, 382
 - electric field strength, 380

- Dielectric (*Continued*)
 - electrostriction, 384–385
 - loss tangent and factor, 383
 - power, 384
- Diesel injector, 408f
- Diffuse reflection, 449
- Diffusion
 - activation energy for self-diffusion, 340
 - Brownian motion, 339
 - CES Elements database, 342
 - coefficient, 341–342
 - concentration gradient of red atoms, 340
 - creep deformation, 339
 - diffusion constant, 341
 - diffusive jump, 340f
 - in doping of semiconductors
 - concentration profile of boron, 346f
 - heat flow problems, 347
 - high-purity silicon, 346–347
 - Fick's law, 341–342
 - field gradients, 343
 - in liquids and non-crystalline solids, 343
 - polycrystalline, 342
 - rules-of-thumb, 342
 - in surface hardening of steel
 - carburising, 345
 - concentration profile of carbon, 345f
 - example, 345b
 - transient diffusion problems
 - Fick's law for, 343
 - flux of diffusing atoms, 343–344
 - intermixing by diffusion, 344f
 - vacancies, 339–340
- Dilute acids, 8b
- Dilute alloys
 - solidification, GL2-39
 - microstructure evolution, GL2-39–GL2-41, GL2-40f
 - Pb-Sn phase diagram, GL2-40f
 - Sn-rich phase formation, GL2-41
- Direct pull, 36
- Directions, 14f, 25f
 - Miller indices of, 13, 13f
 - square brackets, 13
- Dislocation(s), 142
 - climb, 347
 - force on, 145f
 - inter-atomic forces, 142
 - line, 142–143
 - making dislocation by cutting, 143f
 - motion, 145f, 237
 - perfect crystal, 143f
 - screw dislocation, 144f
 - slip directions and planes, 144
 - slip displacements, 144
- Dispersion hardening, 150f
- Displacement-limited designs, 251f
 - elastic hinges and couplings, 251
 - materials for, 251
- Displacive transformation, GL2-60
- Dissipation factor. *See* Loss tangent
- Documentation, 42, 516
- Domestic radiator, 542f
- Doping process, 346–347
- Double weighing method, 52–53
- Doubling-time, 599–601
- Drawing, 147f
- Driving force, 35, 565–566
- Dry sliding, 282
- Ductile fracture, 210–211
- Ductile materials, 20
- Ductile-to-brittle transition, 211–212
- Ductility, 4, 132, 263
 - alloys, 154
 - ceramics and glasses, 133
 - crystalline imperfection, 140–142
 - dislocations and plastic flow
 - dislocation line, 142–143
 - inter-atomic forces, 142
 - making dislocation by cutting, 143f
 - perfect crystal, 143f
 - screw dislocation, 144f
 - slip directions and slip planes, 144
 - slip displacements, 144
 - energy-absorbing applications, 132–133
 - example, 132b
 - hardness test, 133
 - lattice resistance, 146
 - line tension, 146
 - measurement, 130
 - perfection
 - bond strength, 138
 - ideal strength, 140f
 - inter-atomic forces, 140
 - single atomic bond, 139f
 - plastic flow in polymers, 146
 - cold drawing, 147f
 - compression by shear banding, 147

- at low temperatures, 146–147
 - PE, PP and nylon, 147
- shear stress motion, 144
 - dislocation motion causes extension, 145f
 - force on dislocation, 145f
 - resistance, 145–146
- strength, 134
- stress–strain curve, 132
- Durability, 474
 - factors, 474f
 - industrial sector, 474–475
- E**
- e-m radiation. *See* Electromagnetic radiation
- Eco-design, material selection for, 614
 - crash barriers, 617
 - function of barrier, 617–618
 - material selection, 618f
 - minimum embodied energy, 617–618
 - mobile barrier selection, 618
 - static and bumper, 617f
 - static barrier selection, 618–619
 - stiffness-limited design, 619
 - material production phase, 614
 - product disposal phase, 616–617
 - guidelines, 616
 - product manufacture phase, 615
 - product use phase, 615
 - energy consumption and fuel economy, 616f
 - energy efficiency in refrigeration, 616
 - fuel efficiency in transport systems, 615
 - rational use of database, 615f
- Eco-information, 605–606
- Elastic deformation, 264
- Elastic design, 156–157, 165
- Elastic energy, 61
 - calculation, 61
 - example, 61b
 - strained material, 61–62
- Elastic extension/compression
 - stiffness, 98
 - tensile or compressive stress, 97
- Elastic hinges, 180
 - box, lid and hinge, 180–181
 - design requirements for, 180f
 - materials, 181f
- Elastic limit, 130
- Elastic modulus, 4, 52
 - atom-scale force-displacement response, 73
 - bond energy, 72
 - bond stiffness, 72f, 73
 - comparing, 73
 - definitions of, 55f
 - elastomers, 74
 - stretching, 74f
 - tangled structure, 74–75
 - section modulus, 166–168
 - stress, 73
 - Young's modulus, 74
- Elastic problems, solutions to
 - See also* Stiffness-limited design
 - beam elastic bending
 - cross-section area and second moments, 100f
 - deflection, 100f
 - using distance, 98–99
 - distributions, 100–102
 - example, 98b, 101b
 - neutral axis, 98
 - stiffness calculation, 99
 - buckling, 103, 104f
 - cross-section loaded in torsion, 97f
 - elastic extension/compression
 - stiffness, 98
 - tensile or compressive stress, 97
 - geometries and load patterns, 97
 - modeling, 96
 - torsion of shafts
 - circular shafts elastic torsion, 102f
 - example, 103b
 - resistance, 102
 - shear stress, 102–103
 - vibrating beams and plates
 - flexural modes, 104–105
 - natural frequency, 103–104
 - natural vibration modes, 104f
- Elastic waves, 304
- Elasticity, 120
 - theory, 146
 - hardened steel ball, 133–134
 - plastic strain, 132
- Elastomers, 59, 558, 586–587
 - cross-links, 72
 - elastic moduli
 - stretching, 74f
 - tangled structure, 74–75
 - microstructural features in, 558f
 - polymers, A-3
 - density, A-8

Elastomers (*Continued*)

- electrical resistivity and dielectric constant, A-18
- fracture toughness, A-14
- melting temperature and glass temperature, A-6
- thermal conductivity and thermal expansion, A-16
- yield strength and tensile strength, A-12
- Young's modulus, A-10

Electrical, magnetic and optical properties, 9f

- dielectric constant, 8–9
- electromagnetic wave, 10
- magnetic fields, 9–10
- requirements, 10b
- resistivity, 8

Electrical conduction, 8, 376

Electrical conductivity

- conductors, 390, 390f
- crystals formation, 389f
- ionic conduction, 388–389
- Pauli exclusion principle, 389–390
- work function, 390

Electrical insulation

- electric plug, 403, 403f
- polymers, 402–403
- with thermal conduction
 - heat sink, 404, 404f
 - microchips cool, 403–404
- thermoset, 403

Electrical properties

- charts for, 385
- design
 - ferroelectric actuation, 407–408
 - materials for radomes, 405
 - microwave heating, 404
 - piezoelectric actuation, 406
 - pyroelectric thermal imaging, 406–407
 - stealth technology, 404–405
 - transmitting electrical power, 402
- dielectric behaviour, 387
- electrical behaviour, 376f
- electrical resistivity, 385
- origins and manipulation
 - dielectric behaviour, 395–396
 - dielectric breakdown, 397–398
 - dielectric loss, 396–397
 - electrical conductivity, 388–390
 - electrical resistance, 391–394

- ferroelectric materials, 400–401
- piezoelectric materials, 398–399
- pyroelectric materials, 399
- semiconductors, 394–395
- strength and dielectric loss, 387–388
- strength and electrical resistivity, 385–386
- thermal conductivity, 385

Electrical resistance

- electron concentrations and mobilities, 392–393
- field, 391
- imperfections, 391f
- scattering centres, 391–392
- thermal vibration, 394
- work hardening, 393

Electro-chemical mechanisms, 475

Electro-polishing, 19

Electrochromic materials, 464

Electroluminescence, 465

Electromagnetic radiation (e-m radiation), 448

- spectrum of, 449f

Electroplating, 503f

Electrostriction, 384–385

Embodied energy, 606

See also Processing energy

- bar charts, 611
 - of basic materials by volume, 612f
 - of basic materials by weight, 612f
- input–output analysis, 606
- of PET, 606
- property charts, 613
 - modulus–embodied energy chart, 613
 - strength–embodied energy chart, 613
- of virgin and recycled plastics, 609t

Embodiment stage, 34–35

Enameling, 503f

End-of-life potential, 607

Endurance limit, charts for, 235

- plotted against tensile strength, 236f
- tensile strength, 235

Energy demands of products, 610

- approximate values for energy, 611f
- product groups, 610–611

Energy loss, 435–436

Energy release rate, 203

- condition for fracture, 204
- derivation, 204
- release of elastic energy, 204f
- slab of material, 203
- and toughness, 204

- Energy-limited design, 251f
 - choosing materials, 251
 - fracture stress, 250
 - springs and containment systems, 249
- Engineering
 - ceramics, 236–237
 - components, 56
 - disasters, 264
- Engineering materials, data for
 - density, A-8
 - electrical resistivity and dielectric constant, A-18
 - fracture toughness, A-14
 - melting temperature and glass temperature, A-6
 - names and applications
 - composites and ceramics, A-5
 - glasses and natural materials, A-5
 - metals and alloys, A-2
 - polymers and foams, A-3
 - thermal conductivity and thermal expansion, A-16
 - yield strength and tensile strength, A-12
 - Young's modulus, A-10
- Entropy, 5, 561
- Environment
 - design for, 598
 - environmental properties, 11–12
 - Prime Objective, 626
- Equilibrium constitution, GL2-5
- Equilibrium solid-state phase changes
 - eutectoid reaction, GL2-50–GL2-51
 - from austenite to pearlite, GL2-52f
 - eutectoid ferrite-cementite microstructure, GL2-51–GL2-52
 - ferrite and cementite plates, GL2-51
 - single solid phase transformation, GL2-51
 - phase transformations in carbon steels, GL2-50
 - from FCC γ -iron to BCC α -iron, GL2-51f
 - nucleation, GL2-50
 - phase transformations in hypo-eutectoid steels, GL2-52
 - ferrite and pearlite microstructures, GL2-53
 - ferrite-pearlite microstructure, GL2-54f
 - iron carbide, GL2-52
 - microstructure evolution, GL2-53f
 - phase reaction, GL2-52
 - precipitation reactions, GL2-48
 - faster diffusion paths, GL2-49–GL2-50
 - faster nucleation, GL2-49–GL2-50
 - Fe-C phase diagram, GL2-50f
 - precipitation hardening, GL2-48–GL2-49
 - slow-cooled Al-Cu alloy microstructure, GL2-49f
 - two-phase region, GL2-49
- Equilibrium solidification
 - binary alloys, 39
 - Cu-Ni phase diagram, 37f
 - of dilute alloys, 39–41
 - grain boundaries, 37f, 38
 - grain structure, 38–39, 38f
 - for heterogeneous nucleation, GL2-36–GL2-38, GL2-37f
 - for homogeneous nucleation, GL2-36–GL2-38, GL2-37f
 - impingement of solid regions, GL2-37f, GL2-38
 - latent heat release, GL2-36
 - phase composition, GL2-39
 - phase reaction, GL2-39
 - of pure metals, GL2-36–GL2-38
- Error function, 314
- Ethical sourcing of raw materials, 621
- Eutectic Al-Si alloy, GL2-43f
- Eutectic alloy solidification, GL2-42f
- Eutectic point, GL2-10, GL2-28f
 - Fe-C phase diagram, 564–565
 - for Pb-Sn system, GL2-10
- Eutectic reaction, GL2-41
- Eutectic solidification, GL2-41
 - eutectic Al-Si alloy, GL2-43f
 - eutectic reaction, GL2-41
 - off-eutectic Al-Si alloy, GL2-43f
 - Pb-Sn phase diagram, GL2-42f
 - phase reaction, GL2-43
 - phase shape elongation, GL2-42–GL2-43
 - proportions of phases, GL2-42
- Eutectoid ferrite-cementite microstructure, GL2-51–GL2-52
- Eutectoid point, GL2-23, GL2-28f
- Eutectoid reaction, GL2-50–GL2-51
 - from austenite to pearlite, GL2-52f
 - eutectoid ferrite-cementite microstructure, GL2-51–GL2-52
 - ferrite and cementite plates, GL2-51
 - single solid phase transformation, GL2-51
- Exchange energy, 429–430
- Extrusion, 523

- F**
- Face-centred cubic (FCC), 3f, 65–66
 cubic unit cell, 4
 interstitial hole size calculation, 22f
 lattice, GL2-23
 metallic elements, 5
 metals, 5
 octahedral hole, 9f
 packed spheres, 5f
 tetrahedral hole, 9f, 24f
- Fail-safe design
 boiler failures, 256
 example, 255b
 leak-before-break criterion, 255
 material with, 254
 maximum pressure equation, 256
 non-destructive testing, 254
 yield-before-break criterion, 255
- Faraday's equation, 490
- Fast fracture, 248
- Fatigue, 201–202, 226
 damage and cracking
 dislocation motion, 237
 in high-cycle fatigue, 237
 in low-cycle fatigue, 238
 high-cycle fatigue and S–N curve, 227–229
 Basquin's law, 229
 example, 230b
 fatigue or endurance limit, 229
 fatigue strength at, 229f
 low-and high-cycle regimes, 230f
 loading of cracked components
 crack growth during, 234f
 cyclic loading, 233f
 in fabricating large structures, 233
 fatigue crack growth, 233
 Paris law, 233–234
 polystyrene ruler, 234b
 safe design against fatigue failure, 234–235
 low-cycle fatigue, 230
 endurance limit, 231f
 manipulating resistance to
 choosing materials, 238
 compressive surface stress, 238–240
 drop in fatigue ratio with, 239f
 fatigue life, 238
 nondestructive testing, 238
 shot peening, 239f
 material damping, 236–237
 problem of fatigue
 amplitude, 227
 cyclic loading, 228f
 initiation-controlled fatigue, 227
 low-amplitude vibration, 227
 low-cycle fatigue, 227
 stress cycling on, 228f
- Fatigue crack growth, 233
 critical crack length calculation, 261
 example, 262b
 Paris' law equation, 261–262
 proof testing, 262–263
- Fatigue cracks, 238–240
- FCC. *See* Face-centred cubic
- Fe-C phase diagram, 564–565, 564f
- Fermi energy, 389–390
- Ferri-magnetic materials, 421–422
- Ferri-magnets, 9–10
- Ferrites, 421, 565
- Ferro-magnetic materials, 418
- Ferro-magnets, 9–10
- Ferroelectric actuation
See also Piezoelectric actuation
 diesel injector, 408f
 injectors for diesel engines, 407–408
- Ferroelectric materials, 384–385
See also Pyroelectric materials
 BaTiO₃, 400
 dielectric constants, 401
 dipole moment, 400f, 401f–401f
 domains, 400
 ferroelectric hysteresis curve, 401f
- Ferrous alloys, 581, 581f, 584–585, 584f
- Ferrous metals, A-2
 density, A-8
 electrical resistivity and dielectric constant, A-18
 fracture toughness, A-14
 melting and glass temperature, A-6
 thermal conductivity and expansion, A16
 yield and tensile strength, A-12
 Young's modulus, A-10
- Fibre
 composites, 590f
 fibre-based materials, 588
 fibre-reinforced polymers, 79

- Fick's law, 341–342
- Fighting corrosion
 - cathodic protection, 497
 - coatings, 497–504
 - corrosion inhibitors, 504
 - corrosion-resistance ranking, 494t
 - crevices, 497
 - fluids trapping, 500f
 - geometry and configuration design, 496–497
 - material choice design, 496
 - materials and coatings, 498t–499t
 - strategies, 493
 - stress corrosion and corrosion-fatigue, 497
 - suppress galvanic attack, 497
- Finishing process. *See* Surface treatment
- Flame retardants, 482
- Flammability, 475
 - characteristics, 476
 - combustion of polymer, 481
 - flame retardants, 482
 - free-radicals reaction, 481
 - metals, 476
 - ratings, 477t
 - spark or cigarette, 481
 - temperature rise, 481f
- Flexural rigidity, 99
- Floor beams, design requirements for, 117t
- Fluorescence, 465
- Flux density. *See* Magnetic induction
- Flywheels. *See* Spinning disks
- Foams, 77
 - applications, A-13
 - cellular solids, 79–80
 - foam modulus, 80
- Forensic fracture mechanics
 - aerosol or fizzy beverage, 252
 - cylindrical pressure vessel, 253f
 - measurements, 253
 - tank specification, 253t
 - tensile stress, 253–254
 - truck-mounted propane tank, 253
 - working pressure, 254
- Forest hardening, 150f
- Fraction, 278–280
- Fracture
 - designing for
 - adhesive bond peeling, 264f
 - adhesive joints, 264
 - materials with low ductility, 263
 - producers, 263
 - stress concentration, 263
 - thicker strip, 263
 - toughness, 200–201
 - measuring, 201f
 - toughness–modulus chart, 207–208
 - toughness–strength chart, 208–209
- Fracture mechanics
 - crack tip plastic zone, 204–205
 - approximate crack lengths for, 207t
 - brittle materials, 205
 - damage tolerance, 206–207
 - example, 206b
 - forms at crack tip, 205f
 - tensile failure stress, 206
 - transition from yield to fracture, 206f
 - energy release rate, 203
 - condition for fracture, 204
 - derivation, 204
 - release of elastic energy, 204f
 - slab of material, 203
 - and toughness, 204
 - lines of force in cracked body, 200f
 - stress intensity and fracture toughness, 200–201
 - example, 202b
 - material property, 202–203
 - measuring fracture toughness, 201f
 - sharp crack of length, 201–202
 - test machine, 202b
 - yield strength, 218f
- Fracture problems, solutions to
 - using non-destructive testing, 248–249
 - sharp cracks concentrate stress, 248
 - stress intensities with short cracks, 250f
- Fracture-limited design
 - fail-safe design
 - boiler failures, 256
 - example, 255b
 - leak-before-break criterion, 255
 - material with, 254
 - maximum pressure equation, 256
 - non-destructive testing, 254
 - yield-before-break criterion, 255
 - fatigue crack growth
 - critical crack length calculation, 261
 - example, 262b
 - Paris' law equation, 261–262
 - proof testing, 262–263
 - forensic fracture mechanics

- Fracture-limited design (*Continued*)
- aerosol or fizzy beverage, 252
 - cylindrical pressure vessel, 253f
 - measurements, 253
 - tank specification, 253t
 - tensile stress, 253–254
 - truck-mounted propane tank, 253
 - working pressure, 254
 - key players in, 249f
 - materials to resist fatigue
 - candidates, 258
 - CFRP sounds, 258
 - comparing, 256
 - con-rods for high-performance engines
 - connecting rod, 257
 - high-performance engine, 256–257
 - rail cracking, 258
 - endurance limit and density, 259f
 - Hatfield crash, 260
 - hydraulic pressure, 261
 - rail-head cracking, 258–260
 - S–N curve for titanium alloy, 259f
 - Fracture-safe design, material indices for
 - displacement-limited designs, 251f
 - elastic hinges and couplings, 251
 - materials for, 251
 - energy-limited design, 251f
 - choosing materials, 251
 - fracture stress, 250
 - springs and containment systems, 249
 - engineering polymers, 249
 - in load-limited design, 249
 - plotting indices on charts
 - K1c–E chart, 252f
 - materials with values, 251–252
 - metals and polymers, 252
 - thumb demands, 251
 - Free variables, 515, 516f
 - Fresnel construction, 454f
 - Friction, 278
 - high friction, 285
 - abrasive additive, 285
 - asbestos dust, 285
 - brake linings, 285
 - in metal processing, 286–287
 - rotary friction welding, 288
 - sticking friction, 288
 - torque, 288
 - welding processes, 287–288
 - plasticity, 279f
 - profile of surface, 279f
 - sliding friction, 280
 - Friction coefficient. *See* Coefficient of friction
 - Friction stir welding, 287f
 - Functional properties, 13
 - Fusion welding, 19, GL2-46
- ## G
- Galvanic attack, 492
 - Galvanic series, 490
 - GFRP. *See* Glass-fiber reinforced polymers
 - Gibbs free energy, 5
 - Glass transition temperature, 75
 - glassy, 75–76
 - modulus variation with temperature, 75f
 - polymer deformation, 76
 - Glass-fiber reinforced polymers (GFRP), 19
 - Glasses, 18, 557
 - applications, A-5
 - atom packing in, 68
 - coatings, 502
 - microstructural features in, 557f
 - microstructure, 585
 - transition temperature, 294–295
 - Glassy, 75–76
 - Good die design, 539
 - Goodman's rule, 231–232
 - Grain(s), 142
 - boundary hardening, 153
 - grain refinement, GL2-52
 - grain-size hardening, 146
 - Guided Learning Unit, GL2-2
- ## H
- Halite structure. *See* Rocksalt structure
 - HALS. *See* Hindered amine stabilisers
 - Hard
 - See also* Soft magnetic devices
 - magnetic devices
 - Alnico alloy, 437
 - applications, 437t
 - coercive fields, 437
 - hysteresis loop, 436f
 - remanence, 436
 - magnetic materials, 9–10
 - magnets, 423
 - materials, 286
 - Hardenability, 61–63, 583

- Hardening mechanisms, 154
- Hardness test, 133
- HB. *See* Horizontal burn
- HCP crystal structure. *See* Hexagonal close-packed crystal structure
- Heat, 294
 - of carbon steels, GL2-60
 - displacive transformation, GL2-60
 - hardenable, GL2-61–GL2-63
 - martensite, GL2-60
 - martensite appearance, GL2-62f
 - martensite transformation, GL2-61f
 - phase transformations, GL2-63
 - quench cracking, GL2-61–GL2-63
 - quenching and tempering effect, GL2-60–GL2-61
 - tempering, GL2-60
 - exchangers, 316
 - aluminum alloys, 317
 - ceramics, 317
 - internal pressure, 316
 - stress, 316
 - sinks
 - electrically insulation, 44f
 - for microchips, 44b
 - translation for, 45t
 - treatment, 20–22
- Heat capacity, 7
 - atom vibration
 - cage of atoms, 302f
 - thermal energy, 302f
 - atoms in motion, 301–303
- Heat-treatable aluminum alloys, 56, 578–579
 - See also* Non-heat-treatable aluminum alloys
 - Al-rich end, GL2-57f
 - for artificial ageing, GL2-56–GL2-58
 - evolution during ageing, GL2-58–GL2-59
 - precipitation, GL2-56
 - TTT diagram, GL2-58f
- Heavily alloyed metals, 236–237
- Heterogeneous nucleation, 569
- Hexagonal cells, 67
- Hexagonal close-packed crystal structure (HCP crystal structure), 571
- HF transformer cores, 45b
 - transformer, 45f
 - translation for, 46t
- High temperature superconductors (HTS), 440
- High-cycle fatigue, 227
 - Basquin's law, 229
 - example, 230b
 - fatigue or endurance limit, 229
 - fatigue strength at, 229f
 - low-and high-cycle regimes, 230f
 - mean stress and variable amplitude
 - cumulative damage, 232
 - example, 231b
 - Goodman's rule, 231–232
 - safety-critical applications, 232–233
- High-heat capacity materials, 7–8
- High-performance engines, con-rods for
 - candidates, 258
 - CFRP sounds, 258
 - comparing, 256
 - connecting rod, 257
 - high-performance engine, 256–257
- Hindered amine stabilisers (HALS), 482
- HIP. *See* Hot isostatic pressing
- HIPing. *See* Hot isostatic pressing (HIP)
- HNO₃. *See* Nitric acid
- Homogeneous nucleation, 569
- Homogenisation, GL2-46
- Hooke's law, 332
 - compression, 60f
 - constraint effect, 60
 - general cubic element, 59
 - loading geometry, 60b
 - Poisson's ratio, 59
 - states, 59f
 - stiffening effect, 61
 - stress to strain ratio, 60
 - in three dimensions, 59
- Horizontal burn (HB), 476
- Hot dip galvanizing, 503f
- Hot forming
 - process, 332
 - temperatures, 350–352
- Hot isostatic pressing (HIP), 521
- Hot tearing, 519
- HTS. *See* High temperature superconductors
- Human capital, 620
- Hybrid materials, 589–590
 - classes, 590–591, 590f
 - composites, making, 591
 - foams, making, 591
 - laminates and sandwich panels, 591–592
- Hybrids, 19
- Hydrocarbon consumption, 599f

Hydrochloric acid (HCl), 482
 Hydrodynamic lubrication, 282
 Hydrolysis reaction, 491
 Hydrostatic pressure, 55
 Hysteresis loop, 422

I

Ideal strength, 140
 'Inadequate profit margin' scenario, 35
 Indices on charts
 computer-aided selection, 113
 using CES software, 113–115
 selection window, 114f
 E-Relative cost chart, 112f
 ranking, 111
 E-ρ chart showing guidelines, 113f
 loading geometry, 112–113
 logarithmic scales, 112
 selection guidelines, 112
 screening, 111
 Infrared (IR), 467
 Initial magnetisation curve, 422–423
 Initiation-controlled fatigue, 227
 Injection moulding, 19, 27f
 Ink-jet printing, 406
 Inorganic solids, 17
 Insulator, 376
 Integration, 623
 human capital, 627
 manufactured capital, 628
 natural capital, 627
 stakeholders concerns, 628
 Inter-diffusion, 340
 Interference
 destructive, 454–456
 light waves, 454
 phase difference, 455f
 wavelength of light, 454
 Intergranular corrosion, 492
 Intermediate phases, GL2-16
 aluminium-copper system, GL2-17f,
 GL2-18
 compounds, GL2-18
 melting points, GL2-16
 silver-strontium system, GL2-17f
 stoichiometry, GL2-16
 Internal energy, GL2-5
 Interstitial holes, GL2-23
 Interstitial space, GL1-9

 carbon steel, GL1-10
 CPH structure, GL1-10
 holes, GL1-10
 Invar alloy, 298
 Ionised water, 486
 Ionization, 488f
 IR. *See* Infrared
 Iron carbide (Fe₃C), GL2-23
 Iron-carbon diagram, GL2-23, GL2-27f
 See also Phase diagrams
 cast irons and carbon steels, GL2-24f
 characteristic of, GL2-23
 eutectic structure, GL2-24
 eutectoid point, GL2-23
 expanded views, GL2-25f
 Fe₃C system, GL2-23
 iron carbide, GL2-26
 peritectic point, GL2-24–GL2-25
 single phases, GL2-25
 Isomorphous phase diagram, GL2-8
 for Cu-Ni system, GL2-8f
 Isotropic material, 58

J

Joining process, 22, 517–518
 design requirements, 526
 joint geometry, 527–528, 527f
 low carbon steels, 578–579
 manufacturing conditions, 528
 material compatibility
 adhesives, 527
 joints between materials, 527
 modes of loading, 527–528, 527f
 physical limits
 process economics, 528–529
 thermal joining processes, 528
 thermal welding, 577–578
 weld cross-section with, 579f
 welding metallurgy, 579–580
 Judicious design, 493

L

Lattice
 points, 67
 resistance, 146, 236–237
 structures, 590f
 Law of Mass Action, 483
 LCA. *See* Life-cycle analysis
 Lead, 336

- density, 5–6
 - diffusion, GL2-45–GL2-46
 - lead-lined containers, 486
 - Leak-before-break criterion, 255
 - materials selecting for, 257f
 - Lever rule, GL2-14–GL2-15, GL2-14f
 - Life-cycle analysis (LCA), 602–605
 - Light, 448
 - panels, 176
 - design requirements, 177t
 - indices, 177
 - maximum stress, 177
 - strength–density chart, 177f
 - strong panels, 176
 - design requirements, 178t
 - metals and composites, 179
 - minimum mass design, 178
 - self-similar shape, 178
 - shaping effect on strength and mass, 179t
 - strength–density chart with, 177f
 - Light levers, 115f
 - for corkscrews, 115
 - design requirements, 116t
 - floor beams, 117t
 - selection of materials, 116f
 - Young's modulus, 115–116
 - Light tie-rod, 175–176
 - design requirements, 176t
 - elastic design, 176
 - specific strength, 176
 - yield strength, 176
 - Limiting oxygen index (LOI), 476
 - Line tension, 146
 - Line-of-sight deposition processes, 529–530
 - Linear temperature dependence, 330
 - Linear thermal expansion coefficient, 295
 - Liquid solidifies, 559–560
 - Liquidus alloys, 563
 - Liquidus line, 7
 - Load-bearing structures, 156–157
 - Load-limited design, 249
 - Lodestone, 418
 - LOI. *See* Limiting oxygen index
 - Long-chain molecules, 587
 - Longitudinal sound velocity, 81–82
 - Lorentz force, 431
 - Loss coefficient, 226–227
 - Loss tangent, 383
 - Low-cycle fatigue, 227
 - endurance limit, 231f
 - fatigue and empirical description, 230f
 - Lubrication
 - boundary-layer, 282
 - solid lubricants, 282–283
 - viscosity of oil, 282
- ## M
- 'Mac-effect' scenario, 36
 - Machining, 20–22, 517–518
 - Magnetic anisotropy, 433
 - Magnetic design
 - flexible magnets
 - binder, 437–438
 - elastomers, 438t
 - ferrite powder, 437
 - hard magnetic devices
 - Alnico alloy, 437
 - applications, 437t
 - coercive fields, 437
 - hysteresis loop, 436f
 - remanence, 436
 - magnetic information storage
 - AMA, 438
 - fine particles, 438–439
 - magnetic read-write head, 439f
 - squareness, 438
 - materials selection for, 433
 - Meissner effect, 439–440
 - SMES systems, 440
 - energy-density, 440–441
 - refrigeration, 440
 - soft magnetic devices, 434f
 - applications, 435t
 - energy loss, 435–436
 - hysteresis loop, 434f
 - magnetic cores, 433–435
 - superconducting magnets, 439
 - Magnetic induction, 418
 - Magnetic information storage
 - AMA, 438
 - fine particles, 438–439
 - magnetic read-write head, 439f
 - squareness, 438
 - Magnetic properties
 - charts for
 - coercive field–curie temperature chart, 427–428
 - remanence–coercive field chart, 424–426

- Magnetic properties (*Continued*)
 - saturation magnetization—Susceptibility chart, 426
 - drilling down
 - atom, 428
 - domains, 430
 - electron-moments, 428–429
 - energy product, 433
 - ferrites, 430
 - Lorentz force, 431
 - magnetic anisotropy, 433
 - magnetic behaviour, 429f
 - magnetised rod, 430
 - orbital and electron spins, 428f
 - paramagnetic material, 429–430
 - saturation magnetization, 431
 - ferri-magnetic materials, 421–422
 - ferro-magnetic materials, 421–422
 - magnetic fields in materials, 420f
 - energy density, 421
 - macroscopic dipole moment, 419–420
 - magnetic flux density, 420b
 - magnetic pressure, 421
 - magnetic fields in vacuum, 418–419
 - electric current, 419
 - magnetic moment and moment-field interaction, 419f
 - solenoid, 418f
 - measurement
 - hysteresis curve, 423
 - hysteresis loops, 424f
 - initial magnetisation curve, 422–423
 - remanent magnetisation, 422
 - soft and hard magnets, 423
 - Magnetisation, 422
 - Magnetostriction, 62–63
 - Manufactured capital, 620
 - Marine heat exchangers, 317
 - Market need, 34
 - Martensite, 60, 577
 - appearance, 61.2–62f
 - transformation, 61.2–61f
 - Mass-law, 82
 - Material consumption, 598
 - carbon fibre, 599
 - engineering materials, 599f
 - growth, 599–601
 - cumulative growth, 601b
 - doubling-time, 599–601
 - exponential growth, 600f
 - growth rate calculation, 600b
 - hydrocarbon consumption, 599f
 - metals, 598
 - polymers, 598
 - strategic materials, 601
 - Material index, 105
 - for elastic design, 105
 - light and stiff beam, 108–111
 - light and stiff panel, 107–108
 - material index, 105
 - minimising material cost, 111
 - minimising weight, 105–106
 - ranking, 105
 - Material properties, 4, 330
 - chemical properties, 10–11
 - design-limiting properties, 12
 - electrical, magnetic and optical properties, 8
 - dielectric constant, 8–9
 - electromagnetic wave, 10
 - magnetic fields, 9–10
 - requirements, 10b
 - environmental properties, 11–12
 - mechanical properties, 4
 - density, 5–6
 - example, 5b
 - glass or PMMA, 4
 - tensile strength, 4
 - thermal properties, 6
 - energy-efficient cookware, 8b
 - heat capacity, 7–8
 - railroad track buckles, 6
 - thermal conductivity and heat capacity, 7
 - Material property charts, 16, 63
 - ABS, 27f
 - anisotropy, 65
 - bar chart, 24
 - modulus, 24f
 - usage, 24b
 - bubble chart, 25–26
 - modulus, 25f
 - usage, 25b
 - core tool, 26
 - data sheets for materials, 23
 - modulus–density chart, 63
 - modulus–relative cost chart, 63
 - for toughness
 - modulus chart, 207
 - strength chart, 208–209

- Material(s), 2
 - ceramics, 17
 - classifying materials, 16
 - compatibility
 - adhesives, 527
 - joins between materials, 527
 - computer-aided information management
 - computer-based resources, 26b
 - injection moulding, 27f
 - software, 26–28
 - cost minimization, 111
 - damping, 236–237
 - development, 3f
 - elastomers, 19
 - engineering materials menu, 17f
 - families, 16
 - glasses, 18
 - hybrids, 19
 - information for design
 - embodiment stage, 37
 - material search space narrowing, 38f
 - materials selection, 37
 - polyethylene, 37–38
 - process choice, 38
 - production establishment, 38
 - liability and compensation, 2
 - life cycle, 602
 - eco-information, 605–606
 - LCA, 602–605
 - material family examples, 18f
 - metals, 17
 - microstructure, 555
 - ceramics and glasses, 557
 - metals, 555–556
 - polymers and elastomers, 558
 - polymers, 18–19
 - production phase, 614
 - set of attributes, 16–17
 - software for, 4
- Material–process compatibility, 517–518, 517f
- Maximum local stress, 174
- Maximum longitudinal stress, 166
- Maximum service temperature, 6, 294–295, 330
- Maxwell-Boltzmann
 - equation, 339
 - problem, 343
- MCM. *See* Multiple-chip module
- Mechanical properties, 4
 - density, 5–6
 - example, 5b
 - glass or PMMA, 4
 - tensile strength, 4
- Megapascals, 54
- Meissner effect, 439–440
- Melting temperature, GL2-7
- MEMS. *See* Microelectro-mechanical systems
- Metal matrix composites (MMCs), 77
- Metal(s), 17
 - alloys with applications, 155t
 - anisotropy, 65
 - applications, A-2
 - casting and wrought alloys, 571
 - deformation processing
 - crystal texture concept, 575
 - development, 574–575
 - grain structure evolution, 574f, 575
 - material strength, 573–574
 - recovery and recrystallisation, 575
 - solid-state, 573
 - flame spraying, 503f
 - forming
 - example, 183b
 - metal-working operations, 183–185
 - by plasticity, 183
 - processes, 184f
 - rolling of plate with, 183
 - heat treatment
 - normalising, 576
 - plain carbon steels, 577, 578f
 - precipitation hardening, 577
 - quench and temper treatment, 577
 - shaped component, 576
 - thermal profile for, 576f
 - yield strength, 577
 - metal–matrix composites, 149–150
 - microstructure, 556f, 571
 - polymer composites, A-5
 - density, A-8
 - melting and glass temperature, A-6
 - shaping, 521
 - solidification in metal casting, 572f
 - multi-parameter problem, 572–573
 - nucleation, 572
 - porosity, 573
 - segregation, 573
 - steels, 571
 - strength–toughness, 217
 - stress–strain curve for, 57f, 131f

- Metal(s) (*Continued*)
 - thermal welding, 577–578
- Metallic alloy, GL2-3
 - processing of, GL2-4
- Metallic coatings, 501
- Metallic reflectors, 460
- Metals processing
 - See also* Non-metals processing
 - alloy steels and heat treatment, 583
 - brake disks, 581, 581f
 - cast irons, 581–582, 582f
 - deformation processing
 - crystal texture concept, 575
 - development, 574–575
 - grain structure during forming, 575
 - grain structure evolution, 574f
 - material strength, 573–574
 - recovery and recrystallisation, 575
 - solid-state, 573
 - ferrous alloys, 581, 581f
 - ferrous alloys, 584–585, 584f
 - heat treatment
 - normalising, 576
 - plain carbon steels, 577, 578f
 - precipitation hardening, 577
 - quench and temper treatment, 577
 - shaped component, 576
 - thermal profile for, 576f
 - yield strength, 577
 - I-beams, cars and cans, 581f, 582–583
 - joining processes
 - low carbon steels, 578–579
 - thermal welding, 577–578
 - weld cross-section with, 579f
 - welding metallurgy, 579–580
 - solidification, 571
 - in metal casting, 572f
 - multi-parameter problem, 572–573
 - nucleation, 572
 - porosity, 573
 - segregation, 573
 - stainless steel, 583–584
 - surface engineering
 - direct diffusion of atoms, 580
 - laser hardening, 580f
 - transformation hardening, 580
- Metastable phase. *See* Martensite
- micro-farads (μF), 382
- Microelectro-mechanical systems (MEMS), 522
- Microstructure, 552
 - example, 552
 - hybrid materials, 589–590
 - composites, making, 591
 - foams, making, 591
 - laminates and sandwich panels, 591–592
 - materials, 555
 - ceramics and glasses, 557
 - metals, 555–556
 - polymers and elastomers, 558
 - metals processing, 571
 - alloy steels and heat treatment, 583
 - cast iron and brake disk, 581–582
 - casting and wrought alloys, 571
 - deformation processing, 573–575
 - ferrous alloys, 581, 584–585
 - heat treatment, 576–577
 - I-beams, cars and cans, 582–583
 - joining processes, 577–580
 - solidification, 571–573
 - stainless steel, 583–584
 - steels, 571
 - surface engineering, 580
 - non-metals processing
 - ceramics and glasses, 585
 - polymer fibres, 587–588
 - polymer moulding, 587
 - polymers and elastomers, 586–587
 - powder processing, 586
 - processing for properties
 - aluminum bike frames, 553–555
 - bike frame manufacture, 554f
- Microstructure evolution in processing
 - driving force and mechanism, 559
 - liquid solidifies, 559–560
 - nucleation
 - critical radius for, 568
 - and growth, 568, 568f
 - homogeneous nucleation, 569
 - temperature-dependence, 568–569
 - phase, 559
 - diagrams, 559
 - transformation, 559
 - phase diagram, 559
 - Al-Cu system, 563–564, 563f
 - binary Fe-C system, 564–565, 564f
 - for binary Pb-Sn system, 562f
 - real alloys, 561
 - shaping processes, 559

- solidification and heat treatment, 571
 - solidification and precipitation, 560
 - thermodynamics
 - composition, 560
 - entropy, 561
 - equilibrium, 561
 - internal energy, 560–561
 - and kinetics, 565–568
 - materials processing, 560
 - TTT diagrams, 569–570, 570f
 - C-curve shape, 570
 - critical cooling rate, 570
 - temperature against transformation rate, 569f
 - Microwave heating, 404
 - Miller indices, GL1-11
 - procedure for, GL1-12f
 - round brackets, GL1-11
 - Miner's rule, 232–233
 - Minimum embodied energy, 617–618
 - Minimum mass design, 616
 - Minimum service temperatures, 294–295, 330
 - MMCs. *See* Metal matrix composites
 - Mobile barrier selection, 618
 - Mode 1 stress intensity factor, 200–201
 - Mode of loading, 527–528
 - for joints, 527f
 - and states of stress, 54f
 - Modeling, 96
 - Modulus manipulation
 - atomic packing and bonding, 77
 - composites, 77
 - boundaries, 78
 - composite density, 78
 - example, 78b
 - fibre-reinforced polymers, 79
 - geometry or shape, 78
 - manipulation, 77f
 - reinforcement, 79f
 - foams, 79
 - cellular solids, 79–80
 - foam modulus, 80
 - modulus–density chart, 63
 - modulus–relative cost chart, 63
 - modulus–strength chart, 138
 - Molar concentration, 483
 - Molybdenum disulfide (MoS_2), 282–283
 - Monkman–Grant law, 335–336
 - Monolithic-shaped materials, 591–592
 - MoS_2 . *See* Molybdenum disulfide
 - Moulded polymers, 526
 - Moulding, 22, 523
 - Mrotection methods, 474–475
 - Mullite, GL2-28–GL2-29
 - Multi-parameter problem, 572–573
 - Multiple-chip module (MCM), 403–404
 - Mushy zone, 518–519
 - Natural capital, 620
 - Natural composites, A-5
 - density, A-8
 - electrical resistivity and dielectric constant, A-14
 - fracture toughness, A-6
 - melting and glass temperature, A-6
 - thermal conductivity and expansion, A-16
 - yield and tensile strength, A-12
 - Young's modulus, A-10
- ## N
- Natural materials, names and applications, A-5
 - NDT. *See* Non-destructive testing
 - Near-net-shape processes, 553
 - Nernst equation, 489
 - Net flux model, 304–305
 - Newton's law, 332
 - Nickel, 583–584
 - Nitric acid (HNO_3), 482
 - Nitriding, 286
 - Nominal stress–nominal strain, 134–135
 - Non-destructive testing (NDT), 233
 - fail-safe design, 254
 - manipulating geometry and loads, 248–249
 - Non-equilibrium solid-state phase changes, GL2-55
 - See also* Equilibrium solid-state phase changes
 - heat-treatable aluminum alloys, GL2-56
 - Al-rich end, GL2-57f
 - for artificial ageing, GL2-56–GL2-58
 - evolution during ageing, GL2-58–GL2-59
 - precipitation, GL2-56
 - TTT diagram, GL2-58f
 - heat-treatment of carbon steels, GL2-60
 - displacive transformation, GL2-60
 - hardenability, GL2-61–GL2-63
 - martensite, GL2-60
 - martensite appearance, GL2-62f
 - martensite transformation, GL2-61f
 - phase transformations, GL2-63
 - quench cracking, GL2-61–GL2-63

Non-equilibrium solid-state phase changes

(Continued)

quenching and tempering effect,

GL2-60–GL2-61

tempering, 60

non-heat-treatable aluminum alloys,

GL2-55–GL2-56

Non-heat-treatable aluminum alloys,

GL2-55–GL2-56

Non-metals processing

See also Metals processing

ceramics and glasses, 585

polymers

and elastomers, 586–587

polymer fibres, 587–588, 589f

polymer moulding, 587

powder processing, 586, 586f

Nonferrous metals, A-2

density, A-8

electrical resistivity and dielectric constant,
A-18

fracture toughness, A-14

melting and glass temperature, A-6

thermal conductivity and expansion, A-16

yield and tensile strength, A-12

Young's modulus, A-10

Nonlinear temperature dependence, 330–331

Nucleation, 572

critical radius for, 568

and growth, 568, 568f

heterogeneous, 569

homogeneous, 569

temperature-dependence, 568–569

Nylon, 182

O

Objective function

beam, light and stiff, 108

panel, light and stiff, 107

tie-rod, light and stiff, 106

Off-eutectic Al-Si alloy, GL2-43f, GL2-45

Off-eutectic alloy solidification, GL2-42f

Off-eutectic composition solidification, GL2-43

metastable phase, GL2-45

microstructure evolution, GL2-43–GL2-44,
GL2-44f

Pb-rich and Sn-rich regions, GL2-44

Opaque, 448–449

Optical

fibres, 466f

path length, 454–456

profilometry, 524–525

Optical design

using interference, 467

angle of incidence, 467–468

layering effects, 467

methods, 465

using reflection and refraction, 466

refractive index of, 466f

using total internal reflection, 466–467

Optical properties

charts for, 456–457

physics and manipulation of

bakelite, 462

band gap, 463

dichroic materials, 464–465

dielectric, 458, 461

doping, 463–464

e-m wave, 458

electrochromic materials, 464

electroluminescence, 465

electrons, 462

fluorescence, 465

metallic reflectors, 460

metals, 460

Phosphorescence, 465

photochromic materials, 464

photoconductivity, 465

photon, 460

photon energy, 459b

radiation, 459

scattering, 462

thermochromic materials, 464

wavelengths, 461–462

reflectivity and refractive index, 457

refractive index and dielectric constant, 456

Oxidation

growth

metal ion diffusion and electron conduction,
479f

oxygen ion and holes diffusion, 479f

linear weight gain and loss, 480

mass of oxide, 478

measurement, 476f

oxide film, 478

polymers, 475

rate of oxidation, 477

rates of metals, 475

- resistance to metals, 480–481
- weight gain, 477–478
- Oxidation corrosion, differential, 492
- Oxide(s)
 - with corundum structure, GL1-17–GL1-18, GL1-18f
 - film, 478
 - with fluorite structure, GL1-18–GL1-19, GL1-18f
- P**
- Padding, 119
- Paint spraying, 503f
- Paris law, 233–234, 261–262
- Parison, 587
- Particulate composites, 590f
- Partition, GL2-7
- Passive coatings, 500–501
 - See also Active coatings
- Pauli exclusion principle, 389–390
- Pb-Sn system, GL2-13f
 - constitution points, GL2-12f
 - eutectic point for, GL2-10
 - single-phase fields, GL2-11f
 - solubility limits, GL2-11f
- Pb-Sn system. See Binary lead-tin system
- PC. See Polycarbonate
- PE. See Polyethylene
- Pearlite. See Eutectoid ferrite-cementite microstructure
- Peritectic point, GL2-24–GL2-25, GL2-27–GL2-28, 28f
- Peritectoid point, GL2-27–GL2-28, GL2-28f
- Permeability, relative, 419–420
- Permeability of vacuum, 419
- PET. See Polyethylene-terephthalate
- pF. See pico-farads
- Phase diagrams, GL2-2, GL2-6
 - Al-Cu system, 563–564, 563f
 - binary diagram, GL2-9
 - constitution point, GL2-10–GL2-12
 - phase composition, GL2-12–GL2-13
 - solidus boundaries, GL2-9
 - tie-line, GL2-10–GL2-12
 - binary Fe-C system, 564–565, 564f
 - for binary Pb-Sn system, 562f
 - cooling curve, GL2-36f
 - eutectic point, GL2-10, GL2-28f
 - for Pb-Sn system, GL2-10
 - eutectoid point, GL2-28f
 - intermediate phases, GL2-16
 - aluminium-copper system, GL2-17f, GL2-18
 - compounds, GL2-18
 - melting points, GL2-16
 - silver-strontium system, GL2-17f
 - stoichiometry, GL2-16
 - isomorphous, GL2-8
 - partial phase diagram, GL2-10f
 - for Pb-Sn system, GL2-13f
 - constitution points, GL2-12f
 - single-phase fields, GL2-11f
 - solubility limits, GL2-11f
 - peritectic point, GL2-27–GL2-28, GL2-28f
 - peritectoid point, GL2-27–GL2-28, GL2-28f
 - proportions of phases, GL2-14–GL2-15
 - lever rule, GL2-14–GL2-15, GL2-14f
 - weight fractions, GL2-15
 - for pure iron, GL2-36f
 - for pure substance, GL2-7f
 - real alloys can, 561
 - solubility limits, GL2-8
 - solvus boundaries, GL2-9
 - for sugar and tea, GL2-9f
- Phase transformations, GL2-2, GL2-34, 559
 - in carbon steels, GL2-50
 - from FCC γ -iron to BCC α -iron, GL2-51f
 - nucleation, GL2-50
 - diffusion and rate, 568
 - enthalpy and entropy, 566
 - equilibrium solidification
 - binary alloys, GL2-39
 - Cu-Ni phase diagram, GL2-37f
 - of dilute alloys, GL2-39–GL2-41
 - grain boundaries, GL2-37f, GL2-38
 - grain structure, GL2-38–GL2-39, GL2-38f
 - for heterogeneous nucleation, GL2-36–GL2-38, GL2-37f
 - for homogeneous nucleation, GL2-36–GL2-38, GL2-37f
 - impingement of solid regions, GL2-37f, GL2-38
 - latent heat release, GL2-36
 - phase composition, GL2-39
 - phase reaction, GL2-39
 - of pure metals, GL2-36–GL2-38
 - equilibrium state, 565–566
 - eutectic solidification, GL2-41
 - eutectic Al-Si alloy, GL2-43f
 - eutectic reaction, GL2-41
 - off-eutectic Al-Si alloy, GL2-43f

Phase transformations (*Continued*)

- Pb-Sn phase diagram, GL2-42f
- phase reaction, GL2-43
- phase shape elongation, GL2-42–GL2-43
- proportions of phases, GL2-42
- free energy with temperature, 565f
- in hypo-eutectoid steels, GL2-52
 - ferrite and pearlite microstructures, GL2-53, GL2-54f
 - iron carbide, GL2-52
 - microstructure evolution, GL2-53f
 - phase reaction, GL2-52
- kinetic mechanism, 567
- liquid and solid force, 566
- off-eutectic composition solidification, GL2-43
 - metastable phase, GL2-45
 - microstructure evolution, GL2-43–GL2-44, GL2-44f
 - Pb-rich and Sn-rich regions, GL2-44
- precipitate coarsening, 566
- recrystallisation wipes, 567
- segregation, GL2-45–GL2-46
 - consequence of, GL2-46
 - fusion welding, GL2-46
 - homogenisation, GL2-46
 - and impurities, GL2-46
 - solidification cracking, GL2-46
 - in solidification of binary alloys, GL2-46f
- solid-state phase changes, 566
- techniques for quantifying phases, GL2-35t
- thermodynamics and kinetics, GL2-35
- variation, 567f
- Phase(s), GL2-2, GL2-4, 559
 - boundaries, 7
 - change, 319
 - composition, GL2-12–GL2-13
 - diagrams, 559
 - proportions of, GL2-14–GL2-15
 - lever rule, GL2-14–GL2-15, GL2-14f
 - weight fractions, GL2-15
 - reaction, GL2-39
- Phonons, 304
 - conduction, 304–305
 - transmission of heat, 305f
- Phosphorescence, 465
- Photo-degradation, 477
 - commercial polymers, 482
 - ultraviolet absorbers, 482
- Photo-oxidation. *See* Photo-degradation
- Photochromic materials, 464
- Photochromics, 464
- Photoconductivity, 465
- Physical properties, 13
- Physical vapor deposition (PVD), 465
- pico-farads (pF), 382
- Piezoelectric actuation
 - ink-jet printers, 406
 - piezo print-head, 406, 406f
- Piezoelectric coefficient, 384–385
- Piezoelectric materials, 62–63, 384–385
 - in crystals, 398–399
 - dipole moment, 398f
 - strain, 399
 - ultrasonics, 399
- Pinning, 149
- Pitting corrosion, 492
- Plain carbon steel, 581f, 582–583
- Plane bearings, 284
 - See also* Rolling bearings
 - hydrodynamic lubrication, 284
 - soft and hard metals, 284
- Planes, GL1-11, GL1-12f, GL1-24f
 - close-packed planes ways, GL1-20f
 - HCP structure, GL1-10f
 - Miller indices, GL1-11
- Plastic flow
 - dislocation line, 142–143
 - inter-atomic forces, 142
 - making dislocation by cutting, 143f
 - perfect crystal, 143f
 - in polymers, 146
 - cold drawing, 147f
 - compression by shear banding, 147
 - at low temperatures, 146–147
 - PE, PP and nylon, 147
 - screw dislocation, 144f
 - slip directions and slip planes, 144
 - slip displacements, 144
- Plastic work
 - plastic strain, 132
 - polymer–matrix composite, 132
 - for polymers, 130–132
 - true stress and true strain, 134–135
 - difference, 136
 - example, 135b
 - hardness scales comparing, 134f
 - nominal and true stress-strain curves, 136f
 - plastic deformation, 136

- yield strength, 130
- Plasticity problems, 166
 - corkscrew levers, 180
 - elastic hinges and couplings
 - box, lid and hinge, 180–181
 - design requirements for, 180t
 - materials, 181f
 - metal forming
 - example, 183b
 - metal-working operations, 183–185
 - by plasticity, 183
 - processes, 184f
 - rolling of plate with, 183
 - springs
 - choice of materials, 182
 - design requirements for, 183t
 - materials for, 182
 - standard solutions to
 - contact stresses, 172–173
 - spinning disks, 171–172
 - stress concentrations, 173–175
 - yielding of beams and panels, 166–169
 - yielding of shafts, 169–170
 - yielding of ties and columns, 166
 - toughness, 180
 - types, 179–180
- Plastics, 18–19
 - deformation, 264
 - section modulus, 168–169
- Plotting indices on charts
 - K_{1c} - E chart, 252f
 - materials with values, 251–252
 - metals and polymers, 252
 - thumb demands, 251
- Plotting limits on charts
 - computer-aided selection, 113
 - using CES software, 113–115
 - selection window, 114f
 - E -Relative cost chart, 112f
 - screening, 111
- PMC. *See* Polymer matrix composite
- PMMA. *See* Polymethyl-methacrylate
- Poisoning, 581–582
- Poisson's ratio, 58
- Polarisation, 399
- Polarisation, spontaneous, 399
- Polycarbonate (PC), 71
- Polycrystalline material
 - resolution of stress, 154f
 - in tension, 153
- Polyethylene (PE), 24b, 69
- Polyethylene-terephthalate (PET), 598
 - embodied energy of, 606
 - processing energy of, 606–607
- Polymer foams, A-3
 - density, A-8
 - electrical resistivity and dielectric constant, A-18
 - fracture toughness, A-14
 - melting temperature and glass temperature, A-6
 - thermal conductivity and thermal expansion, A-10
 - yield strength and tensile strength, A-12
 - Young's modulus, A-10
- Polymer matrix composite (PMC), 77, 132
- Polymer(s), 18–19
 - applications, A-2
 - atom packing
 - common polymers, 70f
 - elastomers, 72
 - polymer chains, 69f
 - polymer molecules bond, 69–71
 - polymer structures, 69
 - polypropylene form spaghetti-like tangles, 71f
 - structures for silica, 69f
 - thermoplastics weak bonds, 71
 - cluster, 138
 - coatings, 500
 - crystals
 - engineering polymers, GL1-20
 - low symmetry, GL1-19
 - structure of crystalline polyethylene, GL1-19f
 - fibres, 587–588, 589f
 - microstructural features in, 558f
 - molecules bond, 69–71
 - moulding
 - blow moulding, 587
 - molecular architecture evolution, 588f
 - polymers shrink, 587
 - powder spraying, 503f
 - real, 354
 - rheology, 354
 - strength-toughness, 217–218
 - stress-strain curve for, 131f
 - tensile stress-strain curves for, 57f
- Polymethyl-methacrylate (PMMA), 71
- Polyphosphates, 504
- Polypropylene (PP), 598
- Polystyrene (PS), 71, 457

- Polystyrene CD case, 43f
- Polyvinyl chloride (PVC), 598
- 'Poor value for money' scenario, 35
- Porcelain, 17
- Porous composites, A-5
 - density, A-8
 - electrical resistivity and dielectric constant, A-18
 - fracture toughness, A-14
 - melting and glass temperature, A-6
 - thermal conductivity and expansion, A-16
 - yield and tensile strength, A-12
- Young's modulus, A-10
- Porous materials, 82
- Porous solids, 82
- Power, 297
 - methods, 521
 - processing, 586, 586f
 - throwing, 529–530
 - transmitting electrical, 402
 - electrical loss, 402
 - hybrid cable, 402f
 - lowest resistivity, 402
- Power-law creep, 333
- PP. *See* Polypropylene
- PPP thinking
 - See also* Prosperity, Planet, People thinking
- Precipitate coarsening, 566
- Precipitation, 560
 - hardening, 146, 577
 - process, 149–150
 - reactions, GL2-48
 - Al-Cu alloy microstructure, GL2-49f
 - faster diffusion paths, GL2-49–GL2-50
 - faster nucleation, GL2-49–GL2-50
 - Fe-C phase diagram, GL2-50f
 - precipitation hardening, GL2-48–GL2-49
 - two-phase region, GL2-49
- Pressure vessels, GL2-52
- Prime Objective, 621f
 - achieving, 623
 - for sustainability, 622–623
 - for wind farms, 624, 626
- Prismatic shapes, 523
- Process, 19
 - classes of process, 20f
 - classifying processes
 - finishing adds cost, 22
 - hierarchical classification, 22
 - joining process, 22
 - primary and secondary processes, 20–22
 - taxonomy, 22f, 23f
 - computer-aided information management for computer-based resources, 26b
 - injection moulding, 27f
 - software, 26–28
 - ductile materials, 20
 - economics, 528–529
 - information for design
 - embodiment stage, 37
 - establishment of production, 38
 - material search space narrowing, 38f
 - materials selection, 37
 - polyethylene, 37–38
 - process choice, 38
 - manufacturing processes, 21f
 - selection in design
 - constraints, 514
 - documentation, 516
 - free variables, 515, 516f
 - manufacturing processes, 514
 - ranking, 516
 - screening, 515–516
 - translation, 515
 - selection strategy, 515f
 - constraints, 514
 - manufacturing processes, 514
- Process attributes, 516
 - material and process selection, 518
 - Material–process compatibility, 517–518, 517f
- Process-property interaction
 - heat-treating glass, 23
 - welding, 23
- Processing energy, 606–607
 - See also* Recycling energy
 - end-of-life potential, 607
 - energy inputs, 607
 - of PET, 606–607
- Product disposal phase, 616–617
- Product manufacture phase, 615
- Product use phase, 615
 - energy consumption and fuel economy, 616f
 - energy efficiency in refrigeration, 616
 - fuel efficiency in transport systems, 615
- 'Product-recall' scenario, 35
- Proof testing, 254
- Property charts, 52, 613

- modulus—embodied energy chart, 613
- strength—embodied energy chart, 613
- Prosperity, Planet, People thinking (PPP thinking), 619
- Protective coatings, 493
- PS. *See* Polystyrene
- Pure iron, 564
- PVC. *See* Polyvinyl chloride
- PVD. *See* Physical vapor deposition
- Pyrex material, 309
- Pyroelectric
 - materials, 384–385
 - dipole moment, 399
 - electrodes, 399
 - polarisation, 399
 - thermal imaging, 407f
 - filming of wildlife, 406
 - heat-diffusion, 406–407

Q

- Quench cracking, GL2-61–GL2-63

R

- Radiation factor, 83–84
- Radio and microwaves, 448
- Radome, 405, 405f
- Rail cracking, 258
 - endurance limit and density, 259f
 - Hatfield crash, 260
 - hydraulic pressure, 261
 - rail-head cracking, 258–260
 - S–N curve for titanium alloy, 259f
- Random substitutional solid solution, 149
- Ranking, 41, 516
- Recovery, 560, 574f, 575
- Recrystallisation, 560, 567, 575
- Recycled plastics
 - embodied energy, 609t
 - market price, 609t
- Recycling energy, 607
 - down-cycling, 607–608
 - embodied energy of recycled plastics, 609t
 - energy saving, 609
 - energy-absorbing steps, 609t
 - ideals, 607–608
 - in-house scrap, 607–608
 - material fractional contribution, 609
 - of plastics to recover PET, 608f
- Reflection, 623, 629

- Reflectivity, 448
- Refraction
 - example, 453b
 - Fresnel construction, 454f
 - index of, 451
 - reflection, 452–453
 - total internal reflection, 451
 - wave-fronts, 453
- Refrigeration, 440
- Reinforcement, 156
- Remanence. *See* Remanent magnetisation
- Remanence—Coercive field chart
 - electrical resistivity, 425–426
 - soft and hard magnetic materials, 424
- Remanent magnetisation, 422
- Repetition, 226
- Resistivity, 377
 - property, 8
 - temperature-dependence of, 378–379
- Resonance, 226–227
- RMS. *See* Root-mean-square
- Rocksalt structure
 - of magnesia, GL1-17f
 - oxygen ions, GL1-16
 - Sodium chloride, GL1-16
- Rolling, 522
- Rolling bearings
 - deformation of components, 284
 - rolling-contact, 284
 - rotation, 285
- Root-mean-square (RMS), 524
- Rotary friction welding, 287f
- Rubbery behaviour, 75–76
- Rules-of-thumb, 342

S

- Sandwich panels, 590f
- Saturation
 - magnetization, 9–10, 431–433
 - magnetization—susceptibility chart, 426
 - polarisation, 400
- SBR. *See* Styrene butadiene rubber
- Scattering centers, 306–307
- Screening, 515–516
- Screw dislocation, 144f
- Segmented materials, 590f
- Segregation, 45–46, 573
 - chemical, 212
 - consequence of, GL2-46

- Segregation (*Continued*)
 - fusion welding, GL2-46
 - homogenisation, GL2-46
 - and impurities, GL2-46
 - solidification cracking, GL2-46
 - in solidification of binary alloys, GL2-46f
- Selective corrosion, 492
 - corrosion fatigue, 493
 - intergranular corrosion, 492
 - polymers, 493
 - stress corrosion cracking, 492–493
- Semiconductors
 - free electron densities and carrier mobilities, 394–395, 395f
 - intrinsic and extrinsic, 394
 - valence electrons, 394
- Shape factor, 109
- Shape-memory materials, 319
- Shaping, 519f
 - estimating cost for, 530
 - cost model, 530–533
 - mass and section thickness, 518
 - bar spans, 518
 - second bar chart, 518, 520f
 - physical limits
 - casting and moulding, 519
 - forging or rolling, 521, 522f
 - metal shaping, 521
 - polymer moulding, 519, 521f
 - powder methods, 521
 - viscosity and surface tension, 518–519, 520f
 - shape
 - classification scheme, 522, 523f
 - compatibility matrix, 524f
 - continuous processes, 523
 - prismatic shapes, 523
 - tolerance and roughness, 523, 524t
 - characteristic ranges, 525–526, 525f, 526f
 - moulded polymers, 526
 - optical profilometry, 524–525
 - surface roughness, 524, 525f
- Shear modulus, 58
- Shear strain, 56
- Shear stress
 - calculation, 55
 - motion, 144
 - dislocation motion causes extension, 145f
 - force on dislocation, 145f
 - resistance, 145–146
- Sheet thickness, 528
- SiC. *See* Silicon carbide
- Silica crystallization (SiO_2 crystallization), 68–69
- Silica-alumina system, 2GL2-8–GL2-29, GL2-30f
- Silicon, high-purity, 34
- Silicon carbide (SiC), 15, GL1-68
- Silver-strontium system, GL2-17f
- Simple cubic (SC), GL1-3f
- Single phase, GL2-4, GL2-8
 - austenite field, 565
 - for binary Fe-C system, 564f
 - fields, 562f
- SiO_2 crystallization. *See* Silica crystallization
- Sliding bearings, 282
- Sliding friction, 280
- Slip directions, 144
- Slip displacements, 144
- Slip planes, 144
- SMES systems. *See* Superconducting magnetic energy storage systems
- S–N curve, 227–229
 - Basquin's law, 229
 - example, 230b
 - fatigue or endurance limit, 229
 - fatigue strength at, 229f
 - low-and high-cycle regimes, 230f
- Snell's law, 451
- Sodium chloride, GL1-16
- Soft magnetic devices, 434f
 - See also* Hard—magnetic devices
 - applications, 435t
 - energy loss, 435–436
 - hysteresis loop, 434f
 - magnetic cores, 433–435
- Soft magnets, 423
- Soft porous materials, 82
- Solenoid, 418f
- Solid lubricants, 282–283
- Solid solution, GL2-4
 - hardening, 146
- Solid-state deformation processes, 573
- Solid-state phase, 566
- Solidification, 560, 571
 - cracking, GL2-46
 - in metal casting, 572f
 - multi-parameter problem, 572–573
 - nucleation, 572
 - porosity, 573
 - segregation, 573

- Solidus alloy, 563
- Solidus line, GL2-7
- Solution hardening, 149, 150f
- Solvus boundaries, GL2-9
- Sound, 80–81
 - energy radiation
 - acoustic impedances, 84t
 - mass-law, 83
 - radiation factor, 83–84
 - sound boards, 83
 - sound velocity, 85f
 - sound-transmitting material, 83
 - insulation, 82
 - management
 - absorbing and insulation, 82
 - impact noise, 82–83
 - soft porous materials, 82
 - sound insulation, 82
 - wave impedance
 - acoustic impedances, 84t
 - mass-law, 83
 - radiation factor, 83–84
 - sound boards, 83
 - sound velocity, 85f
 - sound-transmitting material, 83
 - waves, 305–306
- Sound-absorption coefficient, 82
- Sound-transmitting material, 83
- Specific heat. *See* Heat capacity
- Specular reflection, 449
- Spinel, GL2-28
- Spinning disks, 171f
 - example, 171b
 - inertial energy storage, 171–172
- Spray-coating process, 530
- Spring-loaded plunger, 120
- Springs
 - choice of materials, 182
 - design requirements for, 183t
 - materials for, 182
- Squareness, 438
- Stainless steel, 581f, 583–584
- Stakeholders, 623–624
 - for sustainability, 623
 - of wind farms, 628f
 - carbon footprint, 626f
 - design, 625
 - environment, 626
 - materials and manufacture, 625
 - regulation, 626
 - society, 627
- Standard reduction potential, 487
- Static coefficient, 280
- Static crash barrier, 617f
 - selection, 618–619
- Static loads, 240
- Stealth technology
 - aircraft, 405
 - using dielectric loss, 404
- Steel connecting rod shaping, 539, 539f
 - carbon steel components, 540
 - constraints, 539–540
 - forging, 541
 - forging and powder methods, 540t
 - process cost model input data, 541f, 541t
 - translation for, 540t
- Steel radiator joining, 541–542, 543t
 - Cambridge Engineering Selector, 542–543
 - domestic radiator, 542f
 - quality and economic criteria, 543
 - translation for, 542t
- Steels, 571
 - See also* Carbon steels
 - BCC structure, 66
 - consumption, 598
 - diffusion in surface hardening
 - carburising, 345
 - concentration profile of carbon, 345f
 - example, 345b
 - high-strength, 182
 - phase transformations in hypo-eutectoid, GL2-52
 - ferrite and pearlite microstructures, GL2-53
 - ferrite-pearlite microstructure, GL2-54f
 - iron carbide, GL2-52
 - microstructure evolution, GL2-53f
 - phase reaction, GL2-52
 - plain carbon, 577, 578f
 - stainless, 583–584
- Sticking friction, 288
- Stiff springs, 303
- Stiffness, 52, 96, 220
 - atom packing
 - amorphous structures, 67f
 - balls on pool table, 65f
 - in ceramics, 68
 - crystal lattice, 67
 - in glasses, 68–69
 - in metals, 65–66

- Stiffness (*Continued*)
- in polymers, 69–72
 - square grid of spheres, 66f
 - structures, 66
 - and unit cell, 66
 - cohesive energy and elastic moduli, 72
 - atom-scale force-displacement response, 73
 - bond energy, 72
 - bond stiffness, 72f
 - bond stiffnesses, 73
 - comparing, 73
 - foams or elastomers, 74
 - stress, 73
 - Young's modulus, 74
 - crystallography, 65
 - density and modulus, 76–77
 - glass transition temperature, 75
 - glassy, 75–76
 - modulus variation, 75f
 - polymer deformation, 76
 - origin of density, 76
 - specific, 106
 - Stiffness-limited design, 165, 619
 - See also* Weight minimization
 - bendy design
 - elastic or natural hinges, 121f
 - elasticity, 120
 - exploiting elasticity, 120
 - flexural degrees of freedom, 121f
 - sliding mechanism, 120f
 - spring-loaded plunger, 120
 - strength, 121
 - traditional three-part hinge, 120
 - material indices for elastic design, 105
 - light and stiff beam, 108–111
 - light and stiff panel, 107–108
 - material index, 105
 - minimising material cost, 111
 - minimising weight, 105–106
 - shaping, 179
 - Storage heaters
 - CES software, 319
 - energy, 318–319
 - using heat capacity, 318
 - wind tunnels, 318
 - Stoves, 480
 - Strain, 52
 - definitions of, 55f
 - shear strain, 56
 - stimuli leading to, 62f
 - tensile strain, 56
 - volumetric strain, 56
 - Strategic materials, 601
 - Strength, 198
 - alloys, 154
 - crystalline imperfection, 140–142
 - dislocation and yield strength relationship, 153–154
 - dislocations and plastic flow
 - dislocation line, 142–143
 - inter-atomic forces, 142
 - making dislocation by cutting, 143f
 - perfect crystal, 143f
 - screw dislocation, 144f
 - slip directions and slip planes, 144
 - slip displacements, 144
 - dispersion and precipitate strengthening
 - critical configuration, 151
 - example, 151b
 - precipitation hardening, 151
 - precipitation process, 149–150
 - grain boundary hardening, 153
 - lattice resistance, 146
 - line tension, 146
 - manipulating properties
 - fracture toughness and modulus, 219f
 - metals, 217
 - polymers and composites, 217–218
 - reinforcement with glass or carbon fibres, 218
 - toughening by fibres, 219f
 - material property, 198–199
 - perfection
 - bond strength, 138
 - ideal strength, 140f
 - inter-atomic forces, 140
 - single atomic bond, 139f
 - plastic flow in polymers, 146
 - cold drawing, 147f
 - compression by shear banding, 147
 - at low temperatures, 146–147
 - PE, PP and nylon, 147
 - plastic strain, 132
 - polymer–matrix composite, 132
 - for polymers, 130–132
 - shear stress motion, 144
 - dislocation motion causes extension, 145f
 - force on dislocation, 145f
 - resistance, 145–146

- solution hardening, 149
- strength and ductility of alloys, 154
- strengthening metals
 - crystalline materials, 148
 - dislocation-eye view, 148f
 - mechanisms, 149
 - obstacles to dislocation motion, 148
 - pinning force, 148
- strengthening polymers, 154–156
 - metal alloys with applications, 155t
 - nominal stress-strain curves, 156f
 - strengthening mechanisms, 155f
- successive positions, 151b
- true stress and true strain, 134–135
 - difference, 136
 - example, 135b
 - hardness scales comparing, 134f
 - nominal and true stress-strain curves, 136f
 - plastic deformation, 136
 - work hardening, 152
 - density of dislocations, 152
 - example, 152b
 - strengthening method, 152–153
 - yield strength, 130
- Strength-limited design, 208
- Strength–density chart, 137f
 - comparison, 138
 - example, 137b
 - polymers cluster, 138
 - strength for engineering materials, 137–138
- Stress, 52
 - corrosion cracking, 492–493
 - definitions of, 55f
 - engineering components, 56
 - example, 54b
 - gradient, 343
 - hydrostatic pressure, 55
 - loading and states modes, 54f
 - megapascals, 54
 - shear stress calculation, 55
- Stress concentration, 173
 - factor, 174
- Stress-free strain, 62–63
- Stressors, 602–605
- Structured data, 26–28
- Styrene butadiene rubber (SBR), 437
- Subgrains, 575
- Sulfuric acid (H_2SO_4), 482
- Super-alloys, 354
- Super-capacitors, 382
- Super-elastic materials, 319
- Superconducting magnetic energy storage systems (SMES systems), 440
 - energy-density, 440–441
 - refrigeration, 440
- Superconducting magnets, 439
- Superconductivity, 376
- Superconductors
 - critical temperatures, 379–380, 380f
 - magnetic field, 379
 - transition to zero resistivity, 379f
- Surface energy, 209
- Surface engineering
 - direct diffusion of atoms, 580
 - laser hardening, 580f
 - transformation hardening, 580
- Surface hardening
 - ball bearing races, 543, 544f
 - CES system, 543–544
 - documentation, 544
 - short-list of processes, 545t
 - translation for, 544t
- Surface roughness, 524
- Surface treatment, 20–22, 517–518
 - design functions, 529t
 - material compatibility, 529
 - physical limits to surface treatments, 530
 - purpose of treatment, 529
 - secondary compatibilities, 529–530
- Sustainability, 619
 - 3BL, 619
 - competing articulations of, 621f
 - sustainability analysis, 622
 - sustainable technology, 621
 - design for, 598
 - fact-finding, 623
 - integration, 623
 - net comprehensive capital, 620
 - pressure for economic growth, 620–621
 - Prime Objective, 622–623
 - reflection on alternatives, 623
 - stakeholders involvement, 623
 - three capitals, 620
 - weak, 620
 - wind farms, 624
 - fact-finding, 625–627
 - integration, 627–628
 - Prime Objectives and scale, 624

- Sustainability (*Continued*)
 reflection, 629
 stakeholders, 624
- Sustainable development, 619
- 'Sustainable technology' scenario, 36
- T**
- Taylor factor, 154
- TBC. *See* Thermal barrier coating
- Technical composites, A-5
 density, A-8
 electrical resistivity and dielectric constant, A-18
 fracture toughness, A-14
 thermal conductivity and expansion, A-16
 yield and tensile strength, A-12
 Young's modulus, A-10
- Temperature dependence
 creep damage and fracture, 335
 creep-rupture diagrams, 335
 example, 336b
 creep testing and curves, 333
 activation energy for, 334
 constitutive model, 334–335
 creep rate, 334f
 primary creep strains, 333
 strain rate, 334
- creep
 deformation, 332
 hot forming process, 332
 linear and nonlinear temperature dependence, 330
 of material properties, 330
 maximum and minimum service temperatures, 330
 rate of straining, 331f
 viscous flow, 332
- Tempering, GL2-60
- Tensile failure, 214
 bending strength, 217
 example, 215b
 flaw controls failure, 216–217
 probability, 216
 statistical distribution, 214
 strength and toughness, 218f
 survival probability, 215f
 in tension and pure bending, 216f
 Weibull equation, 215–216
 weibull statistics, 214
- Tensile strain, 56
- Tensile strength, 198
- Tensile stress, 53
 intensity, 248
- Theoretical density, 8
 FCC nickel, GL1-8b
- Thermal
 buffers
 food warmers, 319
 using phase change, 319
 conductivity, 297
 aluminum alloys strength, 307
 elastic waves, 304
 example, 306b
 free electrons, 306
 net flux model, 304–305
 scattering centers, 306–307
 sound waves, 305–306
 thermal insulators, 307
 diffusivity, 7–8, 298
 distortion management, 311
 expansion
 nonlinear effect, 303
 oscillation of atoms, 304f
 stiff springs, 303
 thermal stress, 306
 tungsten, 303–304
 gradients, 311
 history, GL2-2
 insulators, 307
 joining processes, 528
 problems in manufacturing, 312
 sensing and actuation, 310
 shock resistance, 311–312
 walls insulation, 317
 welding, 577–578
- Thermal barrier coating (TBC), 360
 ceramics, 360
 gas turbines, 359
- Thermal properties, 6
 charts, 298
 thermal conductivity, 298
 thermal expansion, 299f
 yield strength, 300
- design
 heat exchangers, 316–317
 shape-memory and super-elastic materials, 319–320
 storage heaters, 318–319
 thermal buffers, 319

- thermal distortion management, 311
- thermal problems in manufacturing, 312
- thermal sensing and actuation, 310–311
- thermal shock resistance, 311–312
- thermal stress management, 307–309
- thermal walls insulation, 317–318
- transient heat flow problems, 312–315
- energy-efficient cookware, 8b
- examples, 295b
- heat capacity, 7
- linear thermal expansion coefficient, 295–297
- manipulation
 - thermal conductivity and heat capacity, 306–307
 - thermal expansion, 306
- non-crystalline molecular materials, 294–295
- physics
 - heat capacity, 301–303
 - thermal conductivity, 304–306
 - thermal expansion, 303–304
- power, 297
- railroad track buckles, 6
- thermal conductivity, 297
- thermal diffusivity, 298
- Thermal stress, 306
- Thermal stress management, 307–308
 - difference in expansion, 309
 - differential thermal expansion, 308
 - expansion coefficients, 309
 - Pyrex, 309
 - thin film, 308
- Thermochromics, 464
- Thermodynamics
 - composition, 560
 - entropy, 561
 - equilibrium, 561
 - internal energy, 560–561
 - and kinetics of phase transformations
 - diffusion and rate, 568
 - enthalpy and entropy, 566
 - equilibrium state, 565–566
 - free energy with temperature, 565f
 - kinetic mechanism, 567
 - liquid and solid force, 566
 - precipitate coarsening, 566
 - recrystallisation wipes, 567
 - solid-state phase changes, 566
 - variation, 567f
 - materials processing, 560
- Thermoplastic CD case shaping
 - good die design, 539
 - jewel cases of CDs, 538
 - screening, 538–539
 - surviving processes, 539t
 - translation for, 538t
- Thermoplastic polymers, A-3
 - density, A-8
 - electrical resistivity and dielectric constant, A-18
 - fracture toughness, A-14
 - melting and glass temperature, A-6
 - thermal conductivity and expansion, A-16
 - yield and tensile strength, A-12
 - Young's modulus, A-10
- Thermoplastics, 69
 - deformation of, 147f
 - moulding, 587
 - semi-crystalline, 75
 - weak bonds, 71
- Thermoset polymers, A-3
 - density, A-8
 - electrical resistivity and dielectric constant, A-18
 - fracture toughness, A-14
 - melting and glass temperature, A-6
 - thermal conductivity and expansion, A-16
 - yield and tensile strength, A-12
 - Young's modulus, A-10
- Thiourea ($C(NH_2)_2S$), 504
- 3BL. *See* Triple Bottom Line
- Throwing power, 529–530
- Tie-rod, 175–176
 - design requirements, 176t
 - elastic design, 176
 - specific strength, 176
 - yield strength, 176
- Ties, 166
- Time-temperature-transformation (TTT), 2, 569–570
 - C-curve shape, 570
 - critical cooling rate, 570
 - temperature against transformation rate, 569f
- Titanium alloys, 4, 182, 339
- Titanium nitride (TiN), 529
- Torsion of shafts
 - circular shafts elastic torsion, 102f
 - example, 103b
 - resistance, 102
 - shear stress, 102–103

- Torsional rigidity, 102–103
 - Tough ductile fracture, 211
 - ductile metals, 210–211
 - plastic deformation, 211
 - plastic zone forms, 212f
 - plasticity, 211f
 - Toughness, 198
 - atomic bonds, 209f
 - brittle cleavage fracture, 210
 - chemical segregation, 212
 - ductile-to-brittle transition, 211–212
 - manipulating properties
 - fracture toughness and modulus, 219f
 - metals, 217
 - polymers and composites, 217–218
 - reinforcement with glass or carbon fibres, 218
 - toughening by fibres, 219f
 - material property, 198–199
 - fracture toughness–modulus chart, 207–208
 - fracture toughness–strength chart, 208–209
 - surface energy, 209
 - tear and impact test, 199f
 - tests for toughness, 199–200
 - tough and brittle behavior, 199f
 - Transformation hardening, 580
 - Transient diffusion problems
 - Fick's law for, 343
 - flux of diffusing atoms, 343–344
 - intermixing by diffusion, 344f
 - Transient heat flow problems
 - cooling progresses, 313f
 - differential equation, 313–314
 - rule-of-thumb, 315
 - stages of cooling, 315
 - stages of quenching, 314
 - steady-state, 312–313
 - Translation, 515
 - boundary conditions, 40
 - CD case, 43b
 - constraints and objectives, 40t
 - corkscrew lever, 42b
 - distinctions, 40–41
 - heat sinks
 - electrically insulation, 44f
 - for microchips, 44b
 - translation for, 45t
 - HF transformer cores, 45b
 - transformer, 45f
 - translation for, 46t
 - outcome, 41
 - for redesigned CD case, 44t
 - strategy applied to materials, 40f
 - Translucent light, 448–449
 - Transmission, 450–451
 - Transmittability, 448
 - Transmitting electrical power, 402
 - electrical loss, 402
 - hybrid cable, 402f
 - lowest resistivity, 402
 - Transparent light, 448–449
 - Tribological properties, 274
 - coefficient of friction, 274–275
 - wear rate, 275–276
 - Tribologists, 274
 - Triclinic unit cell, GL1-3f
 - Triple Bottom Line (3BL), 619–620
 - Truck-mounted propane tank, 253
 - True stress and strain, 134–135
 - difference, 136
 - example, 135b
 - hardness scales comparing, 134f
 - nominal and true stress-strain curves, 136f
 - plastic deformation, 136
 - TTT. *See* Time-temperature-transformation
 - Tungsten, 303–304
 - Tungsten carbide (WC), 68
 - Turbine blades
 - centrifugal forces, 358–359
 - pressurised pipe, 357f
 - strengthening methods, 359
 - stress, 358
 - stress–rupture time data, 357f
- ## U
- Ultrasonic testing, 254
 - Ultraviolet (UV), 467
 - absorbers, 482
 - Underwriters Laboratory (UL), 476
 - Unit cell, GL1-2
 - compounds, 68f
 - stacked to fill space, 68f
 - Unstructured data, 26–28
- ## V
- Vegard's law, 76–77
 - Vibrating beams

- flexural modes, 104–105
 - natural frequency, 103–104
 - natural vibration modes, 104f
 - Vibration, 119–120, 226–227
 - Visco-elastic solids, 352
 - Viscous flow, 332
- W**
- Wave-fronts, 453
 - WC. *See* Tungsten carbide
 - Wear
 - abrasive, 280–281
 - adhesion, 281
 - adhesive, 280
 - waging war on, 285
 - bearing pressure, 286f
 - CES software, 286
 - hard materials, 286
 - lubrication, 285
 - rotational velocities, 286
 - Wear rate, 275–276
 - Wear rate, specific, 275–276
 - Wear rate–hardness chart, 277
 - Weibull distribution, 214
 - Weibull modulus, 214
 - Weight
 - density, 52
 - gain, 477–478
 - origin of density, 76
 - polymer structures, 69
 - stress, 53
 - Weight minimization
 - See also* Stiffness-limited design
 - light, strong panels, 176
 - design requirements, 177t
 - indices, 177
 - maximum stress, 177
 - strength–density chart, 177f
 - light, strong tie-rod, 175–176
 - design requirements, 176t
 - elastic design, 176
 - specific strength, 176
 - yield strength, 176
 - light and stiff beam, 108
 - comparing materials, 109
 - design requirements for, 109t
 - example, 109b
 - objective function for, 108
 - shape factor, 109
 - shape on bending stiffness, 110f
 - shaping, 109–111
 - shaping on stiffness and mass, 110t
 - stiffness constraint, 108
 - light and stiff panel, 107
 - bending problem, 108
 - design requirements for, 107t
 - objective function, 107
 - stiffness constraint, 107
 - light and stiff tie-rod, 105–106
 - design requirements, 106t
 - load-carrying component, 105f
 - material index, 106
 - mode of loading, 106
 - objective function, 106
 - specific stiffness, 106
 - material cost or volume, 179
 - minimising material cost, 111
 - Weld metal, 577–578
 - Welding, 22, 233
 - contrasting responses to, 578–579
 - exploit frictional heating, 274
 - explosive, 543
 - friction stir, 287
 - fusion, 587
 - metallurgy, 579–580
 - resistance spot, 543
 - rotary friction, 287, 287f
 - thermal, 528
 - White-metal bearings, 284
 - Wind farms, 624
 - fact-finding, 628f
 - carbon footprint, 626f
 - design, 625
 - environment, 626
 - materials and manufacture, 625
 - regulation, 626
 - society, 627
 - integration, 627
 - human capital, 627
 - manufactured capital, 628
 - natural capital, 627
 - stakeholders concerns, 628
 - Prime Objectives and scale, 624
 - reflection, 629
 - stakeholders, 624
 - Wing-tip displacement, 362

- Work hardening, 146
 - density of dislocations, 152
 - example, 152b
 - strengthening method, 152–153
- Wrought alloys, 571
- Y**
- $\text{YBa}_2\text{Cu}_3\text{O}_7$. *See* Yttrium barium copper oxide (YBCO)
- YBCO. *See* Yttrium barium copper oxide
- Yield strength, 4, 130
 - charts for, 137
 - elastic section modulus, 166–168
 - hardness scales comparing, 134f
 - measurement, 130
 - modulus–strength chart, 138
 - plasticity problems, 166
 - polymer–matrix composite, 132
 - for polymers, 130–132
 - strength–density chart, 137f
 - comparison, 138
 - example, 137b
 - polymers cluster, 138
 - strength for engineering materials, 137–138
 - torque and power, 183
- Yield-before-break criterion, 255
- Yield-limited design, material indices for
 - cost or volume, 179
 - light, strong panels, 176–177
 - light, strong tie-rod, 175–176
 - effect of shape, 178–179
- Yielding, 138
 - of beams and panels, 166
 - beam loaded in bending, 167f
 - elastic section modulus, 166–168
 - example, 167b
 - failure moment, 168
 - plastic bending of beams, 168f
 - plastic section modulus, 168–169
 - of shafts, 169–170
 - elastic torsion of shafts, 170f
 - example, 170b
 - helical springs, 170
 - spinning disks, 171f
 - example, 171b
 - inertial energy storage, 171–172
 - of ties and columns, 166
- Young's modulus, 56, 73
 - bond stiffnesses, 73
 - glass transition effect, 75–76
 - measurement, 62
 - modulus–density chart, 64f
 - modulus–relative cost chart, 64f
 - of polypropylene, 219f
 - temperature-dependence of, 75f
- Yttrium barium copper oxide (YBCO), 379–380, 440