

SEVENTH EDITION


# SHIP CONSTRUCTION

D.J EYRES  
G.J BRUCE

**B  
|  
H**

# Ship Construction

*Seventh edition*



***D. J. Eyres***

M.Sc., F.R.I.N.A.

Formerly Lecturer in Naval Architecture, Department of Maritime Studies,  
Plymouth Polytechnic, (now University of Plymouth)

***G. J. Bruce***

M.B.A., F.R.I.N.A., MSNAME.

Formerly Professor of Shiprepair and Conversion,  
School of Marine Science and Technology, Newcastle University



AMSTERDAM • BOSTON • HEIDELBERG • LONDON • NEW YORK • OXFORD  
PARIS • SAN DIEGO • SAN FRANCISCO • SINGAPORE • SYDNEY • TOKYO  
Butterworth-Heinemann is an imprint of Elsevier



# Contents

Preface	vii
Acknowledgments	ix
<b>Part One Introduction to Shipbuilding</b>	<b>1</b>
1 Basic design of the ship	3
2 Ship dimensions, form, size, or category	11
3 Development of ship types	17
<b>Part Two Materials and Strength of Ships</b>	<b>35</b>
4 Classification societies	37
5 Steels	45
6 Other shipbuilding materials	53
7 Testing of materials	61
8 Stresses to which a ship is subject	67
<b>Part Three Welding and Cutting</b>	<b>79</b>
9 Welding and cutting processes used in shipbuilding	81
10 Welding practice and testing welds	103
<b>Part Four Shipyard Practice</b>	<b>117</b>
11 Shipyard layout	119
12 Design information for production	125
13 Plate and section preparation and machining	135
14 Assembly of ship structure	147
15 Launching	161
<b>Part Five Ship Structure</b>	<b>173</b>
16 Bottom structure	175
17 Shell plating and framing	189

18 Bulkheads and pillars	207
19 Decks, hatches, and superstructures	225
20 Fore end structure	241
21 Aft end structure	249
22 Tanker construction	265
23 Liquefied gas carriers	279
<b>Part Six Outfit</b>	<b>291</b>
24 Cargo lifting arrangements	293
25 Cargo access, handling, and restraint	307
26 Pumping and piping arrangements	315
27 Corrosion control and antifouling systems	327
28 Heating, ventilation, air-conditioning, refrigeration, and insulation	345
<b>Part Seven International Regulations</b>	<b>353</b>
29 International Maritime Organization	355
30 Tonnage	359
31 Load Line Rules	363
32 Structural fire protection	371
<b>Index</b>	<b>377</b>

# Subject Index

*Note:* Page references followed by "f" indicate figure, and by "t" indicate table.

## A

- 'A' brackets, 258–260, 261f
  - construction of, 260
- 'A' class divisions, 372–373
- A60 standard, 372
- Aframax, 13
- Aft end structure, 249–252, 258, 262
- Aft peak, 251f, 259f
- Aft peak bulkhead, 208–209, 213, 218
- After end structure, 273
- After perpendicular (AP), 11–12
- Air pipes, 319, 368–369
- Air-conditioning, 31, 126, 345–346
- Alkyd resin, 334–337
- 'Alternative tonnages', 20
- Aluminum
  - alloy, 53–55, 56f, 65
  - alloy sandwich panels, 57
  - alloy tests, 65
  - alloying elements, 55
  - extrusions, 54, 97
  - fiber-reinforced composites (FRCs), 58–59
  - fire protection, 57
  - high speed ferries, 54
  - numeric designation, 55
  - production, 54–57
  - riveting, 55–57
  - superstructure, 53–54, 57
- Aluminum-to-steel connections, 332f
- Amidships, 11–12
- Anchor stowage, 248
- Annealing, 48
- Annual surveys, 41
- Antifouling paints, 338–339
- Antifouling systems, 337–339
- A-O rating, 372–373

- Assembly, 149–151, 153f
- Assembly plate parts listing, 133f
- Assembly plate parts nesting, 133f
- Association of West European Shipbuilders, 361–362
- Association of Western European Shipyards (AWES), 7–8
- Atmospheric corrosion, 328, 330
- Automatic arc welding, 88f
- Automatic welding with cored wires, 86
- Auxiliary steering gear, 256–258
- Awning deck, 19–20, 19f

## B

- 'B' class divisions, 373
- 'B-60' freeboards, 364
- Backstep weld method, 107, 108f
- Balanced rudders, 254
- Ballast
  - capacity, 24, 29, 177, 184, 214–216, 320
  - dirty system, 316
  - pumping and piping arrangements, 315–318
- Bar keel, 175, 176f
- Barge-carrying ships, 21
- Base line, 12–13
- Bending stress, 68–73
- Beam
  - extreme, 12–13
  - knees, 138–140
  - molded, 12–13
- Bending moments, 20–21, 29, 31, 256, 297
  - in seaway, 68
  - wave, 70f
- Bending stresses, 68–73
  - ship as beam, 71

- Bending stresses (*Continued*)  
 strength deck, 71–73
- Bilge, 126  
 blocks, 162, 163f  
 keel, 197–198, 198f  
 piping arrangement, 315–318, 317f  
 pumping, 315–318  
 scuppers, 318  
 suction, 316  
 wells, 180, 319
- Bimetallic corrosion, 330–331, 330t
- Bitumen, 334–337
- Blast cleaning, 339–340
- Block  
 assembly, 152  
 building, 162, 163f
- Block coefficient correction, 365
- Boiler bearers, 187
- Boot topping region, 342
- Bottom girders, 269
- Bottom structure  
 double, 177–184, 179f, 181f, 182f  
 keels, 175–177, 176f  
 machinery seats, 184–187  
 single, 177, 178f
- Bow  
 doors, 307–308  
 ramps, 308  
 steering arrangements, 248  
 thrust units, 248
- Bracket floors, 180–183
- Brackets, tank side, 192f, 193, 194f
- Breadth, 5, 12–13  
*see also* Beam
- 'Breast hooks', 243, 245f
- Bridge structures, 238
- Brine, 346–348  
 coolers, 349  
 traps, 348–349, 350f
- Brittle fracture, 75–76
- Brittleness, 61
- Buckling, 76–78
- Building berths, 122–123
- Building docks, 122–123, 163f, 170–171
- Building hall, 154–155, 171
- Building slipway, 162
- Bulbous bows, 243–244, 245f
- Buckling, 76–78
- Bulk carriers, 13, 23–26, 25f  
 bottom structure of, 184, 185f  
 bulkhead stool, 213f  
 single shell side block unit, 149f  
 single side skin midship section, 200f, 201f
- Bulk carrier single shell side block unit, 149f
- Bulkhead stool, 210, 213f
- Bulkheads, 207–213, 271  
 watertight, 211f, 212f
- Bulwarks, 235–237, 236f  
 construction, 235–237
- Buoyancy, 67–68
- Butterfly' rig, 297–299
- Butt welds, 190, 197–198
- Butts, 189  
*see also* Butt welds
- C**
- 'C' class divisions, 373
- Cabin module, 154f
- Camber, 12–13
- Canals, 5
- Capesize bulk carriers, 293–294
- Capesize ships, 13
- Car carriers, 26, 27f
- Cargo  
 access, 307–308  
 and ballast tanks, 342  
 pumps, 321  
 restraint, 312–314  
 tank washing, 324–325
- Cargo handling equipment, 23
- Cargo lifting  
*see also* Shipboard cranes
- Cargo ports, 368–369
- Cargo ships  
 dry, 17–23  
 watertight bulkheads spacing,  
 208–209
- Cargo tank  
 protection, 321–324  
 purging and gas freeing, 324  
 ventilators, 321  
 washing, 324–325
- Cathodic protection, 333–334
- Cavitation, 331
- Centre line girder, 250f
- Chain locker, 244–245  
 construction of, 244–245, 246f
- Chain pipes, 244–245, 246f

- Charpy impact test, 63–65, 64f
  - Chemical additions (steel), 47
  - Chemical tankers, 275f, 276
  - Chlorinated rubber, 334–337
  - Classification societies, 6
    - damage repairs, 43
    - hull planned maintenance scheme, 43
    - Lloyd's Register, 38–39
    - periodical surveys, 41–43
    - rules and regulations, 38
    - ship operating in ice, 40
    - structural design programs, 40–41
    - tests for hull materials, 63–65
    - weld tests, 114
  - Clean water ballast, 29, 272
  - Coal tar, 334–337
  - Coastal tanker, 266f
  - Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk (BCH Code), 276
  - Cold frame bending, 144
  - Collision bulkhead, 208–209, 213
  - Community of European Shipyards Associations (CESA) contract form, 7–8
  - Compensated gross tonnage (CGT), 361–362
  - Computer-aided design (CAD), 130–134
  - Computer-aided manufacturing (CAM), 130–134
  - Consumables, 114
  - Container
    - guides, 313f
    - lashing, 312
    - ships, 15, 21, 22f, 202f
    - stackers, 313f
  - Contracts, 7–8
  - Controllable pitch propellers, 260–262
  - Conveyor, 136–138
  - Corrosion, 331
    - electrochemical nature of, 328–330
    - due to immersion, 328
    - nature and forms, 327–333
  - Corrosion allowance, 333
  - Corrosion cell, 329f
  - Corrosion control, 333–337
    - cathodic protection, 333–334
    - paints, 337
    - protective coating, 334–337
  - Corrosion-inhibiting paints, 334–337
  - Corrosion-resistant steels, 50
  - Corrugated bulkheads, 210
  - Cranes, 120
  - Crew protection, 369
  - Cross ties, 164
  - Crude oil carrier, 320–321
  - Cruise ships, 31, 262
  - Cruiser stern, 250f
  - Curved panel, 151
  - Cutting, 98–101
    - gas, 98
    - gouging, 100
    - laser, 100–101
    - metal, 99f
    - plasma-arc, 98–100
    - water jet, 101
  - Cutting machines, plate profile, 138–140
- ## D
- Damage repairs, 43
  - Deadrise, 12–13
  - Deadweight, 12–13
  - Deck, 226–229
    - beams, 105, 229
    - cranes, 294
    - construction, 230f
    - girders, 220, 223, 226, 229, 269
    - loads, 226, 229
    - longitudinals, 269
    - plating, 226–228
    - sheathing, 228f
    - stiffening, 229
    - supports, 227f
    - transverses, 269
  - Deck girders, 269
  - Deckhouses, *see* Superstructures and deckhouses
  - Deep tanks, 214–216
    - construction, 216, 217f
    - testing, 216
  - Depth correction, 365
  - Derrick rigs, 297–305, 299f
    - forces in, 300–303, 302f
    - initial tests and re-tests of, 304–305
  - Design
    - concept, 3–4
    - contract, 3–4
    - one-off, 6–7

Design (*Continued*)

- preliminary, 3–5
  - preparation of, 3–4
  - spiral, 3, 4f
- Det Norske Veritas (DNV), 51
- Dimensions, 5, 11–13, 14f
- Direct line cargo piping arrangements, 322f
- Displacement, 5
- Docking surveys, 41–42
- Docks
- building, 122–123, 170–171
  - floating, 171–172
- Doors
- watertight, 21–23, 41, 213–214, 215f, 368–369
  - weathertight, 214, 240, 308, 318, 368–369
- Double-bottom compartments, testing, 184
- Double-hull oil tanker, 268f
- Double-hull tanker, 28f
- erection sequence for, 156f
- Draft, 5, 14f
- extreme, 12–13
  - molded, 12–13
- Drag chains, 168, 170
- Drilling machines, 140
- Dry cargo bulk carrier, 156f
- Duct keels, 177
- Ductility, 61
- Dye penetrant testing, 112
- E**
- Economic criteria, 3–4
- Egg box structure, 149–151
- construction, 105
- Elastic limit, 62
- Elastomers, 51
- Electric arc welding, 84–93, 85f
- Electric furnaces, 46
- Electric podded propulsors, 262–264
- advantages of, 262
- Electrochemical corrosion, 328–331
- Electro-gas welding, 94
- Electro-slag welding, 94, 95f
- Elephant's foot type cargo lashing, 312, 313f
- Elevators, 311f
- End launches
- arresting arrangements, 168–170, 169f

- building slipway, 162
- launching sequence, 168
- launching ways and cradle, 164–165
- lubricant, 165
- releasing arrangements, 165–168

- Engine seats, 186f
- Entrance, 12–13
- Epoxy resins, 334–337
- Erection welding sequences, 110
- Erosion, 331
- Expansion trunks, 28f, 265, 370
- Extreme beam, 12–13
- Extreme depth, 12–13
- Extreme dimensions, 12–13
- Extreme draft, 12–13
- Extrusion, 54–55

**F**

- Fairing ship lines, 126–131, 132f
- Fatigue failures, 76
- Feeder ships, 15
- Fiber-reinforced composites (FRCs), 58–59
- Fillet welds, 105, 107
- Fire doors, 374–375
- Fire protection, 57
- in cargo ships, 372
  - in high-speed craft, 375
- Fire resistance, 373–375
- Fire zone bulkheads, 374–375
- Fitting out basin, 121, 123f
- Fitting out berth, 121, 148–149
- Flame planers, 140
- Flare, 12–13
- Flat panel, 151
- Flat plate keel, 175, 176f, 189
- Floating docks, 171–172
- Floating production, storage, and offloading vessels (FPSOs), 274
- Floating storage units (FSUs), 274
- Floors, 180
- Flush deck correction, 365
- Flux-cored wires (FCAW), 86
- Folding covers, 232–235
- Fore end construction, 242f
- Fore end structure, 243f, 272–273
- deep tank, 272–273
  - forepeak, 273
  - ice strengthening, 273



- Forecastle, 237, 241, 244–245  
Forty-foot equivalent unit (FEU), 13  
Forward perpendicular (FP), 11–12  
Frame bending, 143–146, 145f  
  cold frame bending, 144  
  robotics, 144–146  
  section profilers, 144  
Framing, 191–193  
  longitudinal, 193  
  transverse, 192–193, 192f  
Freeboard, 12–13  
Freeboard computation, 363–366  
  minimum freeboard, 366  
  timber freeboards, 366  
Freeboard corrections, 365–366  
Freeing arrangements, 370  
Freeing ports, 235, 368–369  
Friction stir welding, 96–97, 97f  
Fully pressurized tanks, 282  
Fully refrigerated tanks, 283
- G**
- Galvanic corrosion, 330–331, 330t  
Galvanic series, 330, 330t  
Gangway and access, 370  
Gap presses, 141f  
Garboard strake, 176f, 178f  
Gas  
  cutting, 98  
  shield arc welding, 89–93  
  welding, 82–84, 83f  
Gas carriers  
  general arrangement, 287–288  
  Lloyd's classification, 288–289  
Gas-freeing fans, 324  
Gas-shielded arc welding process,  
  89–93  
GAZ Transport membrane system, 283  
Gearless carriers, *see* Capesize bulk  
  carriers; Panamax carriers  
General arrangement, 6  
General cargo ship  
  erection sequence for, 155f  
  masts on, 294–295  
  midship section, 199f  
General service pipes, 318–319  
General service pumping, 318–319  
Glass fiber-reinforced plastic (GRP), 58  
Goal-based standards, 38  
Gouging cutting, 100  
Grade E steel, 268t  
Green material, 148, 158  
Greenfield, 120–121  
Gross tonnage (GT), 359–360  
Ground ways, 162, 165  
Guillotines, 140  
Gunwale, rounded, 190–191, 191t, 268t
- H**
- Half beams, 229  
Half block model, 128  
Half breadth, 12–13  
Half siding of keel, 12–13  
Hand cleaning, 340  
Handymax, 13  
Handysize, 13  
Hardness, 61  
Hatch, 229–235  
  coamings, 232  
  covers, 232–235, 233f, 234f  
  opening, 231f  
Highways, 271, 370  
Hawse pipes, 247f, 248  
Heating, *see* Heating, ventilation, and air-  
  conditioning (HVAC)  
Heating, ventilation, and air-conditioning  
  (HVAC), 345  
Heat-line bending, 142–143  
Heat treatment of steels, 48  
Heavy lifting, 300  
  *see also* Patent Stülken derricks  
High speed craft, 204f  
Higher tensile steels, 267–268  
High-pressure water blasting, 340  
High-speed craft, 31–33  
  fire protection in, 375  
  types, 32f  
Hogging, 68  
Hold ventilation, 347f  
Horizontal girders, 216  
Hovercraft, 18f, 31–33  
Hull form, 6, 11–12, 23  
Hull planned maintenance scheme, 43
- I**
- Ice  
  classes, 40  
  strengthening, 195–197

- IMO High-Speed Craft Code (HSC Code), 375
- IMO International Gas Carrier Code, 280–282
- independent tanks, 281
  - integral tanks, 280–281
  - internal insulation tanks, 281
  - membrane tanks, 281
  - secondary barrier protection, 282, 282f
  - semi-membrane tanks, 281
- IMO length, 11–12
- Impact tests, 63–65
- ‘Impingement attack’, 331
- Impressed current antifouling systems, 337
- Impressed current systems, 334, 335f
- Independent tanks, 281
- Independent Type A tanks, 283–286
- Independent Type B tanks, 286
- Inert gas system, 324
- Inner bottom plating, 180
- Insulation, 349, 350f, 372
- A60 standard, 372
- Integral tanks, 280–281
- Intermediate surveys, 41
- Internal deck access ramps, 309f
- Internal insulation tanks, 281
- International Air Pollution Prevention Certificate, 357
- International Association of Classification Societies (IACS), 37–38, 357
- International Certificate of Fitness for the Carriage of Dangerous Chemicals in Bulk, 276
- International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk (IBC Code), 276
- cargo tank types, definition, 276
- International Conference on Tonnage Measurement was convened by the IMO in 1969, 359
- International Convention for the Prevention of Pollution from Ships (MARPOL), 324, 356
- convention, 267, 271
  - tankers, 15, 29–30
- International Convention for the Safety of Life at Sea (SOLAS), 1974, 356, 375
- International Convention on Load Lines of Ships, 1966, 356
- International Convention on the Control of Harmful Antifouling on Ships, 2001, 338
- International Convention on Tonnage Measurement, 1969, 356
- International Conventions for the Safety of Life at Sea, 371
- International Labour Organization (ILO) Convention, 305
- International Load Line Convention Certificate, 357
- International Maritime Organization (IMO)
- oil tanker categories, 15
  - organization of, 355
  - relationship with classification societies, 357
  - relationship with national authorities, 356–357
  - work of, 355–356
- International Sewage Pollution Prevention Certificate, 357
- International Tonnage Certificate, 357, 360–361
- Inverse curve, 144
- In-water surveys, 42
- ISO hole, 313–314
- Isomerized rubber, 334–337
- J**
- ‘Jack-knifing’, 303
- Joining ship sections afloat, 158–159
- K**
- Keel blocks, 162
- Keel rake, 12–13
- Keels, 175–177, 176f
- Killed steels, 47, 86
- Kort nozzle, 262
- Kvaerner-Moss spherical tank, 287f
- L**
- Laser cutting, 100–101
- Laser welding, 95–96
- Lashing points, 313f
- Launching, 161–172, 166f
- arresting arrangements, 168–170, 169f

- building docks, 170–171
  - cradle, 164–165, 169f
  - declivity, 162, 164, 170
  - drag chains, 168, 169f, 170
  - end, 162–170
  - floating docks, 171–172
  - lubricant, 165
  - marine railways, 172
  - releasing arrangements, 165–168, 167f
  - sequence, 168
  - ship lifts, 171
  - side, 170
  - slewing arrangements, 167f
  - triggers, 165–168
  - ways and cradle, 164–165
- Length
- overall (LOA), 11–12
  - between perpendiculars (LBP), 11–12
- Lighter aboard ship (LASH), 21
- Lines plan, 126–128, 127f
- Liquefied gas carriers, 284f
- Liquefied natural gas (LNG), 280
- Liquefied natural gas ships, 283–286
- independent Type A tanks, 283–286
  - independent Type B tanks, 286
  - membrane tanks, 286
  - semi-membrane Type B tanks, 286
- Liquefied petroleum gas (LPG), 279–280
- Liquefied petroleum gas ships, 282–283
- fully pressurized tanks, 282
  - fully refrigerated tanks, 283
  - semi-pressurized (or semi-refrigerated) tanks, 282–283
- Liquid methane carrier, 285f
- Lloyd's classification, 288–289
- Lloyd's length, 11–12
- Lloyd's Register (LR), 38–39, 49–50, 55, 76, 78, 110, 208, 229–232
- classification symbols, 39
- Load Line Convention, 357
- Load line rules
- freeboard assignment conditions, 366–370
  - freeboard computation, 363–366
- Local stresses, 73–75
- Loftwork, 128–130
- scale lofting, 10:1, 130
- Longitudinal bottom framing, 182f, 183
- Longitudinal deck framing, 226, 269
- Longitudinal shear forces, 68
- Longitudinal side framing, 193
- Lubricant, 165

## M

- MacGregor-Navire International AB
- 'Rotoloader', 311
- MacGregor-Navire International AB
- 'Stackcell' system, 313–314
- Machinery
- casings, 370
  - positions, 20–21, 364, 366–369
  - seats, 184–187
  - space openings, 368–369
- Magnetic particle testing, 112
- Mangles, 137
- Manual welding electrodes, 86, 87f
- Manufacture of steels, 46–47
- Marine Environmental Protection Committee (MEPC), 355–356
- Marine pollution prevention, 355–356
- Marine railways, 172
- Maritime Administration (MARAD), USA, 7
- Maritime Safety Committee (MSC), 355–356
- Mast construction, 297
- Masts, 294–297
- Matrix assemblies, *see* Egg box structure
- Mechanical planers, 140
- Mechanical ventilation, 345
- Mega-blocks, 158
- Membrane systems, 288f
- Membrane tanks, 281, 286
- Merchant Shipping Act (1894), 30
- Metal cutting, 99f
- Metal inert gas (MIG) welding, 89–93, 91f
- Mid-deck tanker, 29–30
- Midship section
- bulk carrier, 200f, 201f
  - cargo ship, 192, 199f
  - container ship, 202f
  - refrigerated cargo ship, 348f
  - ro-ro ship, 203f
  - coastal tankers, 266f
- Mild steel, 267
- Millscale, 137, 329f
- Minor assembly, 151

Modern rudders, 254  
 Mold, 58–59  
 Mold loft, 130  
 Molded beam, 12–13  
 Molded depth, 12–13  
 Molded dimensions, 12–13  
 Molded draft, 12–13  
 Monitoring Ship Stresses at Sea, 78  
 Multi-product tankers, 321

## N

Nesting plate, 133f  
 Net tonnage (NT), 360  
 Neutral axis, 69–71  
 New Panamax ships, 15  
 Nondestructive testing, 112–114  
 Normalizing, 48  
 Norwegian Shipbuilders Association and  
 Norwegian Shipowners Association, 7  
 Notation, 39–40  
 Notch  
   ductility, 75–76  
   tough steel, 75–76  
 Numerical flame cutting control system,  
 139f

## O

OECD, 361–362  
 Oil Pollution Act, 1990 (OPA 90), 29  
 Oil tankers, 13, 15, 26–30, 28f  
   longitudinal framing of, 270f  
 Oiltight hatchways, 271  
 Oleo-resinous, 334–337  
 Open floors, 175, 177  
 Open hearth process, 46  
 Open shelter deck, 20  
 Open water stern, 23  
 Outfit modules, 152–154  
 Oxyacetylene flame, 340  
 Oxyacetylene, 82–84, 98  
 Oxygen process, 47

## P

Paint systems on ships, 341–342  
   below waterline, 342  
   superstructures, 342  
   waterline or boot topping region, 342  
 Painting ships, 339–342  
   cargo and ballast tanks, 342

  paint systems on ships, 341–342  
   surface preparation, 339–340  
   temporary protection during building, 341  
 Paints, 334–337  
   corrosion protection by, 337  
   *see also* Protective coatings  
 Panama Canal Authority, 361  
 Panama Canal limits, 15  
 Panama Canal tonnages, 361  
 Panamax, 13, 15  
 Panamax carriers, 293–294  
 Panamax ships, 15  
 Panel assemblies, 122f, 133, 151–152  
 Panting, 73–74  
   additional stiffening for, 195  
   arrangements forward, 196f  
 Parallel middle body, 12–13  
 Passenger ship fire divisions, 374f, 374t  
 Passenger Ship Safety Certificate, 356–357  
 Passenger ships, 30–33  
   superstructures, 238–240  
   watertight bulkhead spacing, 209  
 Patent Stülken derricks, 300  
 Payment schedule, 8  
 Periodical surveys, 41–43  
 Photogrammetry, 158  
 Perpendicular after, 11–12, 14f, 126  
 Perpendicular forward, 11–12, 126  
 Pickling, 340  
 Pig iron, 45–47  
 Piggyback covers, 232–235  
 Pillars, 220–223, 221f  
   construction, 220–223  
   small, 223  
   small solid, 222f  
   spacing of hold, 220  
 Pipe module, 150f  
 Piping arrangements, 320–325  
 Planing machines, 140  
 Plasma welding, 93, 93f  
 Plasma-arc cutting, 98–100  
 Plate  
   butts, 108–110, 189  
   edge preparation, 106f  
   handling in machine shops, 138  
   preparation, 135–138  
   profilers, 144  
   rolls, 141  
   seams, 108–110, 189

- Plate preparation, 135–138
    - heating, 137
    - part preparation, 138–143
    - plate leveling rolls (mangles), 137
    - priming paint, 137
    - shot-blasting, 137
    - stockyard, 136
  - Polyurethane resins, 334–337
  - Pontoon covers, 232–235
  - Poop structure, 238
  - Poppets, 162, 164–165, 166f
  - Portable decks, 311–312
  - Post-Panamax ships, 15
  - Pounding, 74
  - Pounding region, additional stiffening in, 183–184
  - Powder cutting, 98
  - Prefabrication, 147–148
  - Pre-MARPOL tankers, 15
  - Presses, 140–141
  - Primer, 342
  - Priming paint, 137
  - Proof stress, 63
  - Propeller post, 252–254
  - Propellers, 260–262
    - controllable pitch propellers, 260–262
    - nozzle, 263f
    - shrouded propellers, 262
  - Propulsive performance, 5
  - Protective coatings, 334–337
  - Pumping and piping arrangements
    - in cargo ships, 315
    - in tankers, 320–325
  - Purchase, of new vessel, 6–7
- Q**
- Quarter access ramps, 310f
  - Queen Mary 2*, 249, 264
  - Quenching, 48
- R**
- Rabbit, 128, 252–254
  - Racking, 73
  - Radiographic testing, 110, 112, 114
  - Raised quarter deck, 17–19
  - Rake
    - of keel, 12–13
    - of stem, 12–13
  - Ramps, 308–309
  - 'Reefer ships', 349
  - Refrigerated cargo ship, 348f
  - Refrigerated cargo stowage, 346
  - Refrigerated container ships, 349–351
  - Refrigeration, 346–348
  - Register length, 11–12
  - Rimmed steels, 47, 86
  - Ring main cargo piping arrangements, 323f
  - Rise of floor, 12–13, 164
  - Riverside layout, traditional, 119f
  - Riveting aluminum, 55–57
  - Robotics, 107, 144–146
  - Roll-on roll-off (ro-ro) vessels, 21–23, 22f, 203f, 307
    - stern ramps in, 308
  - Rudders, 254–256, 255f
    - bearing, 256, 257f
    - construction, 254
    - pintles, 254–256
    - stock, 256
    - trunk, 256
  - Run, 12–13
- S**
- Sacrificial anode systems, 333
  - Safe working load (SWL), 294
  - Safety convention, 355–357
  - Sagging, 68
  - Sampson posts, 294–297
  - Scale lofting, 10:1, 130
  - Scantling, 19–20, 229
  - Scissor lift, 312
  - Scribe board, 229
  - Scuppers, 318
    - inlets, and discharges, 368–369
  - Sea inlets, 319–320, 320f
  - Seams, 189
  - Secondary barrier protection, 282, 282t
  - Section machining, 123f, 138–143
  - Section preparation, 135–138
  - Section profilers, 144
  - Segregated ballast tanks (SBTs), 267
  - Self-polishing copolymer (SPC) antifouling paints, 338
  - Semi-membrane tanks, 281
  - Semi-membrane Type B tanks, 286
  - Semi-pressurized tanks, 282–283
  - Semi-refrigerated tanks, 282–283
  - Service speed, 6

- Shaft bossing, 258–260, 261f
  - construction of, 260
- Shaft tunnel, 218, 219f
  - construction, 218
- Sheaves, 300–303
- Sheer, 12–13
- Sheer correction, 365
- Sheerstrake, 190
- Shell
  - butts, 108–110, 189
  - expansion, 128, 129f
  - forming, 142f
  - plating, 189–204, 190f
  - bilge keel, 197–198, 198f
  - bottom, 189–190
  - framing, 191–193
  - grades of steel for, 191
  - local strengthening of, 195–197
  - seams, 108–110, 189
  - side, 190–191
  - tank side brackets, 193, 194f
- Shell plating, three-dimensional representations, 128
- Shelter deck, 19–20
- Ship
  - arresting arrangements, 168–170, 169f
  - as beam, 71
  - building process, 122f
  - classification, operating in ice, 40
  - design, 3–5
  - drawing office, 125–128
  - lifts, 171
  - product model, 131–134, 132f
  - releasing arrangements, 165–168, 167f
  - spiral, 4f
  - stresses, 78
  - structure assembly, 147–159
  - types, 18f
- Ship drawing office, 126–128
  - lines plan, 126–128, 127f
  - loftwork followed, 128–130
  - shell expansion, 128, 129f
  - shell plating, three-dimensional representations, 128
- Ship lifts, 171
- Ship openings, 368–369
- Ship product model, 132f
- Ship types, 364t
- Shipboard cranes, 293–294
- Shipbuilders Association of Japan (JSA), 7, 361–362
- Shipbuilding process, 122f, 135
- Shipyards layout, 119–123, 123f
  - modern large, 121f
- Shipyards planning, decisions involved, 121
- Shipyards replanning, decisions involved, 121
- Shot-blasting, 137, 340
- Shrouded propellers, 262
- Side
  - doors, 309–311
  - girders, 183–184
  - launching, 170
  - loaders, 309–311
  - scuttles, 368–369
- Single bottom structure, 177
  - construction, 166f
- Single product carrier, 320–321
- Single pull covers, 232–235
- Single-hull bulk carrier, block erection for, 157f
- Slag-shielded processes, 84–89
- Slewing ramp, 309, 310f
- Sliding ways, 164–165, 170
- Slipways, 119–120, 162
- Small waterplane area, twin hull craft (SWATH), 18f, 31–33, 32f
- Solid plate floors, 180–184, 269
- Sounding pipes, 319
- Spacing of watertight bulkheads:
  - cargo ships, 208–209
  - passenger ships, 209
- Spar deck, 19–20, 19f
- Special category space, protection of, 375
- Special surveys, 42–43
- Special trade passenger (STP) ships, 31
- 'Spectacle frame', 260
- Spurling pipes, 244–245
- Stability, 5
- Standard fire test, 373
- Steel
  - castings, 52
  - chemical addition to, 47
  - construction, 372
  - corrosion-resistant, 50
  - forgings, 52
  - grade, 46

- heat treatment of, 48
  - high tensile, 50
  - Lloyd's requirement for mild, 191t
  - manufacture, 46–47
  - sandwich panels, 50–51
  - sections, 48, 49f
  - shipbuilding, 49
  - Steering gear, 256–258
  - Stem rake, 12–13
  - Stern, 241–243
    - construction, 252
    - doors, 307–308, 308f
    - frame, 252–254, 253f
    - ramps, 308f, 310f
    - tube, 258, 259f
  - Stiffening, 297
    - in mast and heavy derricks, 298f
  - Stockyard, 136
  - Strain, 61–62
  - Strength deck, 71–73
  - Stress, 61–62
    - corrosion, 331
    - relieving, 48
    - and strain relationship, 104f
  - Structural design programs, 40–41
  - Structural fire protection, 371–375
    - requirement, 371–372
    - special category space, 375
    - see also* Fire protection
  - Stud welding, 88–89, 90f
  - Subassembly, 151
  - Submerged arc welding, 86–88
  - Submerged turret loading (STL) system, 274
  - Suez Canal Authority, 361
  - Suez Canal limits, 16
  - Suez Canal tonnages, 361
  - Suezmax, 13
  - Superstructure correction, 365
  - Superstructures, 273–274
  - Superstructures and deckhouses, 237–240
    - bridge structures, 238
    - effective, 238, 239f
    - forecastle, 237
    - passenger ship, 238–240
    - poop structure, 238
    - weathertight doors, 240
  - Surface effect ships (SESSs), 31–33
  - Surface preparation for paint, 339–340
  - Syncrolift, 171
- ## T
- Tack weld, 105
  - Tank
    - cleaning, 30, 271
    - side brackets, 193, 194f
    - top, 177, 180, 193, 210, 223, 349
  - Tank spaces, construction in, 268–269
    - bottom girders, 269
    - deck girders, 269
    - floors and transverses, 269
    - longitudinal framing, 269
  - Tanker construction materials, 267–268
    - higher tensile steel, 267–268
    - mild steel, 267
  - Tankers
    - cargo piping arrangements in, 320–325, 322f
    - cargo pumping arrangements in, 320–325
  - Tempering, 48
  - Template drawing, 130
  - Tensile strength, 61, 63
  - Tensile test, 63
  - Testing
    - deep tanks, 216
    - derrick rigs, 304–305
    - double-bottom compartments, 184
    - material, 61–65
    - rudder, 254
    - tanks, 272
    - watertight bulkheads, 213
  - Thermit welding, 96
  - Three island type, 17, 19–20
  - Timber freeboard, 366
  - Toilet module, 154f
  - Tonnage, 12–13, 20, 356–357, 359–360
    - compensated gross tonnage (CGT), 361–362
    - gross tonnage, 359–360
    - measurement for, 360–361
    - net tonnage, 360
  - Topside tanks, 218
  - Torsion, 73, 74f
  - Toughness, 61
  - Transom stern, 251f
  - Transverse framing, 269

Transverse stresses, 73  
Transverse webs, 193, 195, 268–269, 268f, 273  
Transversely framed double bottom, 180–183  
Trial speed, 6  
Tributyltin compounds (TBTs), 338  
Triggers, 165–168  
Tumblehome, 12–13  
Tungsten inert gas welding, 89  
Turret deck, 24  
Tween deck height, 12–13  
Twenty-foot equivalent unit (TEU), 13  
‘Two-pack paints’, 334–337  
Type ‘A’ ships, 363–365  
    special conditions of assignment, 370  
Type ‘B’ ships, 363–365

**U**

Ultimate strength, 61, 63  
Ultra-large container ships, 15  
Ultra-large crude carrier (ULCC), 13  
Ultrasonic inspection, 114  
Unbalanced rudders, 254  
Union purchase rig, 303  
    forces in, 304f  
Unit:  
    assembly, 151–152  
    erection, 154–158, 155f, 156f, 157f

**V**

Vehicle lashing, 312  
Ventilation, 345–346  
    fire damper, 374f  
Ventilators, 368–369  
Vertical shear and longitudinal bending, in still water, 67–68, 69f  
Vertical stiffeners, 210  
Very large crude carrier (VLCC), 13  
Vinyl resins, 334–337  
Virtual reality, 134  
Visual inspection of welds, 112

**W**

Water blasting, 340  
Water jet cutting, 101  
Watertight bulkheads:  
    construction, 209–210  
    corrugated, 212f  
    plain, 211f  
    spacing, 208–209  
    testing, 213  
Watertight doors, 213–214, 215f  
Wave bending moments, 68, 70f  
Wave piercer, 18f, 31–33  
Weather deck, 26, 226–229, 235, 346, 370  
Weathertight doors, 240  
Weathertight vehicle ramp, 307–308  
Welding  
    automation, 105–107  
    classification society tests and, 114  
    distortion, 107  
    electric arc, 84–93, 85f  
    electro-gas, 94  
    electro-slag, 94, 95f  
    and faults, 110, 111f  
    flux and, 82–88, 94  
    friction stir, 96–97, 97f  
    gas, 82–84, 83f  
    and inspection, 113f  
    laser, 95–96  
    and nondestructive testing, 112–114  
    practice, 103–105  
    sequences, 107–110, 108f  
    and testing, 110  
    thermit, 96  
Wing in ground effect craft (WIG), 18f  
Wire model, 131  
Wood ceiling, 177, 180

**Y**

Yield point, 63

**Z**

Zinc-rich paints, 334–337